

▶ Motor output: 700 m<sup>3</sup>/h

▶ Number of fan motors / exhaust air outlets: 2



### Benefits of edge extraction

- ✓ Large surface, easy-to-clean lower side
- ✓ Very strong suction effect at the four outer edges / optimal extraction output
- ✓ The shield protects the fan motors from heat and insulates noise
- ✓ The low-wear full metal filters can be taken out and cleaned easily in the dishwasher

• ON/OFF switch:	Yes
• Motor Power:	0 m <sup>3</sup> /h to 700 m <sup>3</sup> /h
• Fan regulation:	3-level
• Power load:	0,16 kW   230 V   50 Hz
• Available on request:	-
• Lighting:	yes Can be switched separately
• Including:	Attachment material
• Material:	CNS 18/10
• Important information:	-
• Number of fan motors/ exhaust air outputs:	2
• Flame protection filter:	Type B
• Material filter:	Aluminium
• Lamps (number + watt):	1 x 18 W
• Number of filters:	2
• Properties:	-
• Assembly type:	Wall
• Size:	W 1,000 x D 520 x H 170 mm
• Weight:	21.1 kg

### Intensive power cleaner F1L, set of 2



- Order quantity unit: 1 box (2 bottles)
- Content: 2 x 1 litre
- Ph level: 14
- HACCP compliant: Yes
- Chlorine-free: Yes
- Phosphate-free: Yes
- Including: 1 spray head  
1 spray lance
- Important information: Attention: Not suitable for surfaces sensitive to alkali such aluminium  
Exclusively available in Germany and Austria

Code-No. 173080  
GTIN 4015613731933

### Adapter for hoods 900 and 1000 mm

- Properties: Connection of two outputs (Ø 125 mm) on an output (Ø 150 mm)
- Important information: -
- Material: Metal  
Galvanised
- Size: W 300 x D 150 x H 250 mm
- Weight: 1.4 kg

Code-No. 100103  
GTIN 4015613119342