



- ▶ Table-top warming plate
- ✓ Ideally suited for warm buffets



- ▶ Keeping warm with induction
- ✓ 300 Watt

- ▶ Pot detection
- ✓ Pot diameter max.: 200 - 380 mm

- ▶ Easy operation
- ✓ Temperature control in 5°C steps



- ▶ Combinable
- ✓ 4 appliances can be switched in sequence in 1 power circuit



The design of this hot plate makes every buffet look more appealing. The practical solution of connecting and switching 4 appliances with the optionally available cable in one circuit also ensures a uniform, high-quality look when serving food.

- | | | | |
|-----------------------------------|---------------------------|--|---|
| • Power load: | 0,3 kW 230 V 50-60 Hz | • Combinability: | 4 appliances can be switched in sequence in 1 power circuit |
| • Equipment connection: | Pluggable | • Control panel: | On the appliance |
| • Temperature range: | 40 °C to 95 °C | • Regulation of: | Output |
| • Control unit: | Electronic | • Pot diameter max.: | 200 - 380 mm |
| | Touch | • Estimated delivery time from our warehouse in Salzkotten, Germany is week: | 15 / 2023 |
| • Control lamp: | - | • Size: | W 395 x D 395 x H 98 mm |
| • Size cerane surface: | W 390 x D 390 mm | • Weight: | 5.6 kg |
| • Overheating protection: | Yes | | |
| • Timer: | No | | |
| • Digital display: | Yes | | |
| • ON/OFF switch: | Yes | | |
| • Can be installed: | No | | |
| • Pot recognition: | Yes | | |
| • Lock button (child protection): | No | | |
| • Material hob: | Glass | | |
| • Number of temperature levels: | 12 | | |
| • Intervals temperature setting: | 5 °C | | |
| • Output max.: | 300 W | | |
| • Type of warming station(s): | Induction | | |
| • Number of warming stations: | 1 | | |
| • Material: | Steel | | |
| • Important information: | - | | |
| • Colour: | Black
Silver | | |
| • Properties: | - | | |

