## Induction warming system IWS650



With the "invisible" induction warming system, the worktop can be used either as a warming area or work surface. Installed under a worktop, the impressive technology allows the chafing dish to be heated up to 100 °C while the worktop temperature reaches a maximum of 35 °C.

| <ul> <li>Number of warming<br/>stations:</li> </ul>                         | 1   |
|---|---|
| <ul> <li>Type of warming stati-<br/>on(s):</li> </ul>                       | Induction                                     |
| Suitable worktop mate-<br>rial:   | Glass<br>Ceramic<br>Marble<br>Quartz<br>Stone |
| <ul> <li>Suitable worktop thick-<br/>ness:</li> </ul>                       | 4 - 20 mm                                     |
| <ul> <li>Maximum worktop<br/>temperature:</li> </ul>                        | 35 °C   |
| <ul> <li>Regulation of:</li> </ul>  | Output  |
| Output max.:  | 650 W   |
| <ul> <li>Temperature range in-<br/>duction warming sys-<br/>tem:</li> </ul> | to 55 °C                                      |
| <ul> <li>Number of output le-<br/>vels:</li> </ul>                          | 20  |
| <ul> <li>Temperature range<br/>chafing dish:</li> </ul>                     | Up to 100 °C                                  |
| Control panel:  | Cable length: 2 m<br>Separate                 |
| <ul> <li>Pot recognition:</li> </ul>  | Yes   |
| <ul> <li>Lock button (child pro-<br/>tection):</li> </ul>                   | No  |
| Timer:  | No  |
| <ul> <li>Digital display:</li> </ul>  | Yes   |
| <ul> <li>Overheating protecti-<br/>on:</li> </ul>                           | Yes   |
| ON/OFF switch:  | Yes   |

Subject to technical modifications and error

| <ul><li> Control lamp:</li><li> Control unit:</li></ul> |
|---|
| • Equipment connection:                                 |

- Power load:
- Material:
- Important information:
- Properties:
- Including:
- Suitable worktop mate- 1/1 GN rial:

## • Size:

• Weight:

Electronic Touch Pluggable 0,65 kW | 230 V | 50 Hz Stainless steel Washable air filter 1 spacer 2/3 GN Round up to 40 cm W 390 x D 390 x H 96 mm 10 kg



- Induction warming system for more flexibility
  - ✓ Installation below the worktop
  - ✓ Worktop can be used either as a warming station or work surface




- Temperature range induction warming system: up to 55 °C
- Temperature range chafing dish: up to 100 °C



- Spacer
  - ✓ For optimal heat transfer without heating the work surface
  - Maximum worktop temperature: 35 °C



- Suitable worktop material:
  - ✓ Glass
  - Ceramic
  - ✓ Marble
  - Quartz
- Stone





## Code-No. 105866



## Induction warming system IWS650

Add on Products

