



▶ Performance capacity at 10° d: 1600 litres / day

▶ Cost-effective and environmentally friendly thanks to reduction in required detergent quantity

▶ Monitoring the regenerated water volume with an optionally available water meter

▶ Reduction in lime deposits inside appliance and on washed items due to reduction in water hardness

This water softening unit provides protection against calcification for commercial dishwashers and optimises washing results by reducing lime deposits on washed items. Thanks to the softer water, the use of detergents is minimised.

- Power load: 0,006 kW | 230 V | 50/60 Hz
- Digital display: Yes
- Water intake temperature from: 5 °C
- Water intake temperature to: 35 °C
- Regeneration: Time period
- Water connection: 3/4"
- Colour: White
- Output capacity: 1,600 litres / day at 10° d (total hardness)
- Material: Plastic
- Important information: -
- Connection capacity: 1 unit
- Setting possibilities: Brine dosing
Time
Time-based regeneration
- Designed for: Commercial dishwashers
- Operating pressure: 3 - 6 bar
- Brine tank salt store: 10 kg
- Salt consumption: 0.96 kg / regeneration
- Regeneration time: 95 min.
- Size: W 255 x D 400 x H 420 mm
- Weight: 8.6 kg

Connecting set WEH1600

- Set comprises: 2 armoured hoses AG - water connection 3/4", length 1 m, rated width Ø 15 mm
- Important information: -
- Size: W 420 x D 325 x H 60 mm
- Weight: 1 kg

Code-No. 109885
GTIN 4015613586748