



- Output/h: Up to 60 baskets
- Cycle time: 60 / 90 / 120 / 180 seconds



- Soft start washing pump
- Detachable rinsing nozzles
- Narrow mesh stainless steel sieve



- Double-walled
- Can be fitted below the counter
- We recommend a hot water connection.



4 wash programs, removable rinsing nozzles, a double-walled design, a narrow mesh stainless steel sieve, and a gentle startup thanks to a soft-start washing pump – features that make this dishwasher, which can also be installed under a work surface, truly impressive.

Plate height max.: 340 mm
Door double-walled: Yes
Can be fitted below the counter:

• Glasses height max.: 325 mm

• Power load: 5,15 kW | 400 V | 50 Hz

• Equipment connection: 3 NAC Boiler heater: 4,5 kW 2,7 kW • Tank heater: • Dry-run protection: Yes Control lamp: • ON/OFF switch: Yes • Lye pump: Yes • Water softener: No · Clear rinsing dosing Yes pump:

Door contact switch: Yes
Safety thermostat: Yes
Cleaning agent dosing Yes

pump:

ture:

• Basket dimensions: 500 x 500 mm

• Run-time: 60 / 90 / 120 / 180 seconds

• Output / hour max.: 60 baskets • Self-cleaning: Yes · Cold rinsing: No · Double-walled: Yes · Tank volume: 16,5 litre(s) • Water pressure: 2 - 4 bar G 3/4" M · Water supply: Water outlet: Ø 24 mm 55 °C · Water intake tempera Number of wash programs:

· Display:

· Including:

· Weight:

• Material: CNS 18/10

• Important information: We recommend a warm water

connection

• Properties: Narrow mesh stainless steel sieve

Soft-start washing pump Removable rinsing nozzles Boiler temperature Programme code

1 universal basket 1 plate basket 1 cutlery holder 1 supply hose 1 drainage hose

Tank temperature

• Water consumption at 2.3 litres / wash cycle 2 bar:

• Size: W 600 x D 640 x H 850 mm

67.2 kg





Add on Products

## Glass polisher









• Power load:

• Polishing/drying type:

 Properties: Including:

Material:

· Important information:

• ON/OFF switch:

· Control lamp: • Size:



1,1 kW | 230 V | 50 Hz

Microfibre polishing scarves with hot air fans

Microfibre polishing scarves detachable

Stainless steel

Microfibre

Yes

W 340 x D 305 x H 520 mm

## Full desalination system VK 500 FB



· Desalination type: Full desalination

• Water connection: 3/4" · Colour: Blue Connection capacity: 1 unit

5,000 litres / cartridge at 10° d (total salt con-• Output capacity:

• Material: Plastic Glass-fibre reinforced

• Important information:

290 € • Deposit per cartridge: Sampling tap: Yes

## Water softening system WEH1350







• Power load: 0,03 kW | 230 V | 50/60 Hz

· Digital display:

• Water intake temperature from: 5°C 40 °C • Water intake temperature to: Setting possibilities: Interval

Regeneration Language Time Water hardness

· Regeneration: Flow rate or time period

· Water connection: 3/4"

Code-No. 109889

## Stainl.steel polish.spray 500ml can



Content / can:

· Application: Remove heavy soiling such as grease residue

Do not spray onto hot surfaces

• allow them to cool down first:

· Application:

Before use, bring the can to room temperature

and shake well

Spray sparingly onto the surfaces to be cleaned

Rub evenly over the entire surface Polish with a dry cloth

Code-No. 173031



Add on Products

#### Dishwasher cleaner F10L



• Designed for: Commercial dishwashers

Content: 10 litres
Model: Liquid
HACCP compliant: Yes
Chlorine-free: Yes
Phosphate-free: Yes

Including:
 Application:
 Application concentrations: 1 - 3 g per litre of

water depending on water hardness

Dosing via an automatic dosing system

Properties: Best material compatibility

best material compatibility

Code-No. 17327

#### Dishwasher cleaner F10LXTRA



• Designed for: Commercial dishwashers

Content: 10 litres
Model: Liquid
HACCP compliant: Yes
Chlorine-free: No
Phosphate-free: Yes
Including: -

• Application: Application concentrations: 1,5 - 3,5 g per litre

of water depending on water hardness Dosing via an automatic dosing system Removes even the most stubborn dirt

Properties: Removes even the most stubborn dirt

Code-No. 173271 GTIN 4015613767895

#### Rinsing agent F10L



Model: Liquid
HACCP compliant: Yes
Chlorine-free: Yes
Phosphate-free: Yes

• Including: • Content: 10 litres

• Designed for: Commercial dishwashers

Household dishwashers

Combi steamer with rinsing program

 Application: Application concentrations: 0.2 - 0.4 g per litre of rinsing water depending on water hardness

Code-No. 173272

## Dishwasher basket trolley ASP700







• Can be loaded from both sides: Yes

• Designed for: Dishwasher baskets 500 x 500 mm

• Worktop surface: No

• Properties: Frame in square tubing 25 x 25 mm

One basket guard each on the front and back

Including:

 Model:
 Slots

 Application area:
 Clearing

Storage

Total load-bearing capacity, max.: 100 kgWith handle(s): No

Code-No. 300147



Add on Products

# Water softening system WEH1600



• Power load: 0,006 kW | 230 V | 50/60 Hz

• Digital display: Yes • Water intake temperature from: 5 °C 35 °C • Water intake temperature to: • Regeneration: Time period • Water connection: 3/4" • Colour: White

1,600 litres / day at 10° d (total hardness) • Output capacity:

• Material: Plastic • Important information: Connection capacity: 1 unit

Code-No. 109952