Dishwasher US P500 LPWR





- Output/h: Up to 60 baskets
- Cycle time: 60 / 90 / 120 / 180 seconds



- Soft start washing pump
- Detachable rinsing nozzles
- Narrow mesh stainless steel sieve



- Double-walled
- Can be fitted below the counter
- We recommend a hot water connection.



4 wash programs, removable rinsing nozzles, a double-walled design, a narrow mesh stainless steel sieve, and a gentle startup thanks to a soft-start washing pump – features that make this dishwasher, which can also be installed under a work surface, truly impressive.

• Plate height max.: 340 mm · Door double-walled: Yes • Can be fitted below Yes the counter:

· Glasses height max.: 325 mm

5,15 kW | 400 V | 50 Hz • Power load:

• Equipment connection: 3 NAC Boiler heater: 4,5 kW 2,7 kW • Tank heater: • Dry-run protection: Yes Control lamp: • ON/OFF switch: Yes · Lye pump: Yes • Water softener: Yes · Clear rinsing dosing pump:

• Door contact switch: Yes • Safety thermostat: Yes · Cleaning agent dosing Yes

pump:

ture:

500 x 500 mm · Basket dimensions:

60 / 90 / 120 / 180 seconds • Run-time:

• Output / hour max.: 60 baskets • Self-cleaning: Yes · Cold rinsing: No · Double-walled: Yes · Tank volume: 16,5 litre(s) • Water pressure: 2 - 4 bar G 3/4" M · Water supply: Water outlet: Ø 24 mm 55 °C · Water intake tempera-

Narrow mesh stainless steel sieve • Properties:

Soft-start washing pump Removable rinsing nozzles · Number of wash pro-

· Material: CNS 18/10

· Important information: We recommend a warm water

connection Boiler temperature Programme code

 Water consumption at 2.3 litres / wash cycle 2 bar:

· Including:

grams:

• Display:

· Weight:

1 universal basket

1 plate basket 1 cutlery holder 1 supply hose 1 drainage hose

1 filling funnel for salt W 600 x D 640 x H 850 mm • Size:

68 kg





Dishwasher US P500 LPWR

Add on Products

Glass polisher









• Power load:

• Polishing/drying type:

Properties:

Including:

Material:

· Important information:

 ON/OFF switch: · Control lamp:

• Size:



1,1 kW | 230 V | 50 Hz

Microfibre polishing scarves with hot air fans

Microfibre polishing scarves detachable

Stainless steel Microfibre

Yes

W 340 x D 305 x H 520 mm

Pressure booster pump set DSS10



0,15 kW | 230 V | 50 Hz Power load:

• Important information:

Material:

Properties:

• Set comprises:

• 6.3 μF): • Set comprises:

• Designed for:

Plastic

1 pump (W 100 x D 175 x H 110 mm, 1.5 A)

1 condenser (W 35 x D 120 x H 35 mm

1 hose, rubber

Installation material

Dishwasher US E500 LPR Dishwasher US C500 LP

Stainl.steel polish.spray 500ml can



Content / can:

500 ml

· Application:

Remove heavy soiling such as grease residue

Do not spray onto hot surfaces

• allow them to cool down first:

· Application:

Before use, bring the can to room temperature and shake well

Spray sparingly onto the surfaces to be cleaned

Rub evenly over the entire surface

Polish with a dry cloth

Dishwasher basket trolley ASP700









· Can be loaded from both sides:

· Designed for: Dishwasher baskets 500 x 500 mm

Worktop surface:

• Properties: Frame in square tubing 25 x 25 mm

One basket guard each on the front and back

• Including:

• Model: Slots • Application area: Clearing

Storage

• Total load-bearing capacity, max.: 100 kg · With handle(s):

Code-No. 300147



Dishwasher US P500 LPWR

Add on Products

Dishwasher cleaner F10L



Commercial dishwashers • Designed for:

· Content: 10 litres Model: Liquid • HACCP compliant: Yes • Chlorine-free: Yes · Phosphate-free: Yes Including:

· Application: Application concentrations: 1 - 3 g per litre of

water depending on water hardness Dosing via an automatic dosing system

· Properties: Best material compatibility

Dishwasher cleaner F10LXTRA



• Designed for: Commercial dishwashers

Content: 10 litres • Model: Liquid • HACCP compliant: Yes • Chlorine-free: Nο • Phosphate-free: Yes Including:

· Application: Application concentrations: 1,5 - 3,5 g per litre

of water depending on water hardness Dosing via an automatic dosing system Removes even the most stubborn dirt

· Properties:

Rinsing agent F10L



Model: Liquid · HACCP compliant: Yes • Chlorine-free: Yes • Phosphate-free: Yes

• Including:

Content:

• Designed for: Commercial dishwashers

Household dishwashers

Combi steamer with rinsing program Application concentrations: 0.2 - 0.4 g per litre • Application:

10 litres

of rinsing water depending on water hardness

Code-No. 173272

Water softening system WEH1600



• Power load: 0,006 kW | 230 V | 50/60 Hz

· Digital display: • Water intake temperature from: 5°C 35 °C · Water intake temperature to: Regeneration: Time period 3/4" • Water connection: White · Colour:

• Output capacity: 1,600 litres / day at 10° d (total hardness)

• Material: Plastic • Important information: Connection capacity: 1 unit

Code-No. 109952