## Bartscher



The Bartscher combi steamer from the Silversteam series has 5 shelves in 1/1 GN format – it's the ideal partner for every kitchen. The manual controls enable the easy, on-demand control of all cooking processes.

<ul><li>Power load:</li><li>Equipment connection:</li></ul>	6,3 kW   400 V   50 Hz 3 NAC	Properties:	Rounded baking chamber Bearing rails can be detached
Temperature range:	50 °C to 280 °C		Double-winged door pane
Control unit:	Toggle		LED lighting in door
Functions:	Circulating air		Socket (500 W) for connection of
- Tunctions.	Steam		an extractor hood
	Combi-steaming	LED display:	Steaming
	Low temperature cooking	ELD display.	Core temperature
	Reversing motor direction (fan		Temperature
	wheels)		Time
	Steam production by means of	<ul> <li>Including:</li> </ul>	1 grille 1/1 GN
	direct injection	• Including.	1 tray 1/1 GN
Rack control:	No		1 water supply hose
Hack controll	Yes	Augilable on request:	i water supply nose
<ul> <li>Continuous operation:</li> <li>Vapour extractor:</li> </ul>	Yes	Available on request:	- ON/OFF
	Side	Control lamp:	
<ul> <li>Core temperature sen- sor connection;</li> </ul>	Side	Series:	Temperature Silversteam
<ul> <li>USB connection:</li> </ul>			
	-	Temperature control:	Stepless
Fan speed:	2 levels	Interior lighting:	Yes
<ul> <li>Number of cooking</li> </ul>	1	<ul> <li>Format drawers:</li> </ul>	1/1 GN
programs:	4		600 x 400 mm
Number of cooking	1	Operating mode:	Electro
phases:		With cleaning system:	No
Type of drawers:	Crosswise	Material:	CNS 18/10
Number of drawers:	5	<ul> <li>Important information:</li> </ul>	From a water hardness of 5° d.H
<ul> <li>Distance between trays:</li> </ul>	74 mm		upwards, we urgently recom- mend fitting a suitable water sof-
<ul> <li>Water connection:</li> </ul>	3/4"		tener and a water pressure of
<ul> <li>Time adjustment:</li> </ul>	0 to 120 minutes		maximum 3 bar
<ul> <li>Material cooking</li> </ul>	CNS 18/10	<ul> <li>Size:</li> </ul>	W 930 x D 900 x H 790 mm
chamber:		<ul> <li>Weight:</li> </ul>	82.3 kg
<ul> <li>Number of fans:</li> </ul>	1		


GR

)3/2023 |/1 °C 280

CNS 18/10

4







Double door glazing, inner door can be opened easily for cleaning



Vapour extractor is easy to regulate

Bearing rails can be detached



2 fan speed settings



