



▶ Salamander with 2 heating zones



▶ Cooking grid size

✓ W 590 x D 320 mm



▶ With practical lift function

✓ Clear height: 65 - 210 mm



Ideal starter model with the practical lift function. The Salamander stands out thanks to the simple operation of the two heating zones and the effective radiators.

- | | | | |
|---|----------------------------------|-----------|--------------------------|
| • Power load: | 4 kW 400 V 50/60 Hz | • Size: | W 600 x D 540 x H 530 mm |
| • Equipment connection: | 2 NAC | • Weight: | 47.7 kg |
| • Control unit: | Toggle | | |
| • Height-adjustable grid: | No | | |
| • Number of heating zones: | 2 | | |
| • Digital display: | No | | |
| • Manual time setting: | No | | |
| • Size grid: | B 590 x D 320 mm | | |
| • Warm-keeping function: | No | | |
| • Automatic activation function: | No | | |
| • Properties: | - | | |
| • Energy regulation: | Simmerstat | | |
| • Number of heating elements: | 2 | | |
| • Material: | Stainless steel | | |
| • Important information: | - | | |
| • Clear height: | 65 - 210 mm | | |
| • Control lamp: | Heat up
Operational | | |
| • Temperature range to: | 400 °C | | |
| • Grease collection tank: | Yes | | |
| • Output control: | Stepless
Continuous operation | | |
| • Heating zones can be controlled separately: | Yes | | |
| • Height-adjustable heating element: | Yes | | |
| • Heat source: | Radiant heaters | | |
| • Including: | 1 grille | | |