
Milk frother induction MSI400







• Power load: 0,6 kW | 230 V | 50/60 Hz

· Temperature range: 0 °C to 70 °C

• Automatic turn-off: Yes • ON switch:

• Mixing bowl: Detachable

Stainless steel with plastic lid

• Design: Induction

· Material: Stainless steel

• Important information:

· Properties: 4 non-slip feet made of silicone

Beaker, lid, mixing disks, dish-

washer-suitable

For fresh milk in all fat levels Induction surface with contact switch for stainless steel cups

Cable winding

Milk does not need to be war-

med first

Foaming/heating at 65 °C · Functions:

Foaming/heating at 70 °C 150 ml to 400 ml of milk can be foamed/heated in approx. 80-90

seconds

Cold foaming · Content: 0,4 litre(s) · Control unit: Electronic Knob

· Control lamp: yes Colour. Silver

2 milk froth disks · Including: 1 mixing disk

Frothing, max.: 200 ml

• Filling quantity:

• Size:

• Weight:

Heating, max.: 400 ml W 125 x D 150 x H 180 mm 1.1 kg

Content: 0.4 litres

For fresh milk with all fat contents

No need to preheat the milk

Includes:

✓ 2 milk frothing disks

√ 1 mixing disk





Induction surface with contact switch for stainless steel cups



Filling quantity

✓ Frothing: Max. 200 ml

✓ Heating: Max. 400 ml







• Filling quantity:





