



- Power load: 2 kW | 230 V | 50 Hz
- Temperature range: 30 °C to 90 °C
- Control unit: Electronic  
Toggle
- Protection class: IPX4
- Basin size, GN format: 3 x 1/1 GN
- Control lamp: Heat up  
ON/OFF
- Temperature control: Stepless  
Thermostatic
- Delivery state: Building kit (simple assembly)
- Swivel casters: 4 swivel casters, 2 with brake
- Depth GN container max.: 200 mm
- Heating type: Dry heated
- ON/OFF switch: Yes
- Thermostat: Yes
- Diameter casters: 125 mm
- Length cable: 3 m
- Connection cable type: Spiral cable
- Wheel buffer: 4 units, plastic
- Double-walled basin: Yes
- Not included in delivery: GN containers
- Material: CNS 18/10
- Important information: -
- Water drain tap: No
- Number of tanks: 1
- Heating zones can be controlled separately: No
- Size: W 650 x D 1,200 x H 855 mm
- Weight: 41 kg

### Oil and grease remover F1L



- Content: 6 x 1 litre
- Model: Liquid
- HACCP compliant: Yes
- Chlorine-free: Yes
- Phosphate-free: Yes
- Including: -
- Order quantity unit: 1 box (6 bottles)
- Designed for: Wipe-off work surfaces, stainless steel surfaces  
Tiled walls and floors  
Highly effective against deposits in coffee cans  
Machines, appliances

Code-No. 173276  
GTIN 4015613761176