

- Fan regulation: Via an external controller
- Cut-out for the motor: 232 x 208 mm
- Available on request: Ceiling hood  
Wall hood series 1100  
Other sizes
- Lighting: yes
- Flame protection filter: Type A
- Material filter: CNS 18/10
- Number of filters: 3
- Including: -
- Material: CNS 18/10
- Important information: Can only be commissioned with an additional controller
- Number of fan motors/  
exhaust air outputs: 1
- Power load: 0,202 kW | 230 V | 50-60 Hz
- Operating mode: Exhaust air
- Assembly type: Wall
- Properties: Blare-free light installed with grease protection cover  
Filter carrier with additional grease collection channel
- Motor output: 184 W
- Lamps (number + watt): 1 x 18 W
- Protection class: IP44
- Max. air throughput: 1500 m<sup>3</sup>/h
- Size: W 1,800 x D 900 x H 450 mm
- Weight: 45 kg



### Intensive power cleaner F1L, set of 2



- Order quantity unit: 1 box (2 bottles)
- Content: 2 x 1 litre
- Ph level: 14
- HACCP compliant: Yes
- Chlorine-free: Yes
- Phosphate-free: Yes
- Including: 1 spray head  
1 spray lance
- Important information: Attention: Not suitable for surfaces sensitive to alkali such aluminium  
Exclusively available in Germany and Austria

Code-No. 173080  
GTIN 4015613731933

### Control, steplessly variable



- Important information: -
- Material: Plastic
- Designed for: Extractor hoods with 1 phase
- Protection class: IP54
- Control unit: Toggle
- ON/OFF switch: Yes
- Light switch: Yes
- Output control: Manual  
Stepless
- Assembly type: Wall  
Extractor hood

Code-No. 220110  
GTIN 4015613603056