



▶ Temperature range:

- ✓ -40 °C to 300 °C
- ✓ -58 °F to 572 °F




▶ Digital design

- ✓ Measurement cycle: 3-4 seconds
- ✓ Min./max. memory
- ✓ Display illuminated



▶ With core temperature sensor

- ✓ Puncture depth: 110 mm
- ✓ Fold-away temperature sensor



Watertight thermometer with fold-away core temperature sensor. The large temperature measuring range from -40°C to +300°C is just as convincing as the illuminated display and the min./max. memory.

- | | | | |
|----------------------------------|--|-----------|---------|
| • Control unit: | Electronic | • Weight: | 0.09 kg |
| • Puncture depth: | 110 mm | | |
| • Temperature range: | -40 °C to 300 °C | | |
| • Design: | Digital | | |
| • With temperature sensor: | Yes | | |
| • Colour: | White | | |
| • Temperature measurement units: | °C
°F | | |
| • Material temperature sensor: | Stainless steel | | |
| • Diameter temperature sensor: | 3,5 mm | | |
| • Material: | Plastic ABS | | |
| • Size of display field: | W 48 x H 16.7 mm | | |
| • Protection class: | IP68 | | |
| • Properties: | Fold-away temperature sensor
Display illuminated
Min./max. memory
Automatic shutdown after 60 minutes
Measurement cycle: 3-4 seconds
Watertight
Temperature range also in Fahrenheit | | |
| • Important information: | Do not use in oven | | |
| • Including: | 2 batteries | | |
| • Battery: | Button cell CR2032 | | |
| • Application area: | Steaming
Cooling | | |
| • Designed for: | Core temperature measurements | | |
| • Size: | W 155 x D 45 x H 23 mm | | |