



▶ Temperature range:

- ✓ -50 °C to 300 °C
- ✓ -58 °F to 572 °F



▶ Puncture depth:

- ✓ 120 mm



▶ Designed for:

- ✓ Core temperature measurements
- ✓ Temperature monitoring during transport and storage



It cannot be hot or cold enough: Digital plunge temperature with a very large temperature measurement range – from deep-freeze to food preparation.

- |                                  |  |                          |                        |
|----------------------------------|--|--------------------------|------------------------|
| • Control unit:                  | Electronic   | • Battery:               | Button cell LR754/AG5  |
| • Puncture depth:                | 120 mm   | • Important information: | Do not use in oven     |
| • Application area:              | Canteens<br>Refrigeration cell<br>Freezer cell<br>Refrigerated rooms                       | • Size:                  | W 34 x D 34 x H 160 mm |
| • Temperature range:             | -50 °C to 300 °C   | • Weight:                | 0.02 kg                |
| • Design:                        | Digital  |                          |                        |
| • With temperature sensor:       | Yes  |                          |                        |
| • Designed for:                  | Core temperature measurements<br>Temperature monitoring during transport and storage       |                          |                        |
| • Colour:                        | White<br>Black<br>Red  |                          |                        |
| • Temperature measurement units: | °C<br>°F   |                          |                        |
| • Material temperature sensor:   | Stainless steel  |                          |                        |
| • Diameter temperature sensor:   | 3,8 mm   |                          |                        |
| • Material:                      | Stainless steel<br>Plastic   |                          |                        |
| • Size of display field:         | W 22 x H 10 mm   |                          |                        |
| • Properties:                    | LCD display<br>Temperature range also in Fahrenheit<br>Automatic shutdown after 10 minutes |                          |                        |
| • Including:                     | Protection cap<br>1 battery  |                          |                        |