Vacuum packaging machine K 300/60L



Everything under control: The chamber vacuum packaging machine is equipped with a glass lid and a manometer to monitoring underpressure. A clamp bar in the chamber prevents the vacuuming bag from slipping.

)4/2023 \mathbf{T}

materiar na.	01035
 Power load: 	0,35 kW 230 V 50 Hz
 Control unit: 	Electronic
 ON/OFF switch: 	Yes
Colour:	Silver
	Black
 Length welding rod: 	300 mm
Vacuum control:	Time-controlled
Functions:	Combined vacuuming and se-
	aling
	Manual sealing
	Marinating
• Material	Stainless steel
- Matchal.	Plastic
Important information:	
Chamber dimensions:	- W 305 x D 320 x H 90 mm
	VV 505 X D 520 X H 90 IIIIII
 Lighting: Number of welded 	2
itaniber of fredea	Z
joints:	(0) / min (manual 4 m3 / hours)
Vacuum pump:	60 L / min. (approx. 4 m ³ / hours)
Vacuuming intensity	yes
can be regulated:	
Welding duration can	3 - 9 seconds
be regulated:	
 Including: 	30 vacuuming bags (280 x 330
	mm)
 Properties: 	Vacuuming time: 20 - 99 seconds
	Pressure display via manometer
	Clip for vacuuming bag
 Control lamp: 	Combined vacuuming and se-
	aling

Glass

Control lamp:

- Maximum vacuum: • Digital display:
- Size:
- Sealing Marinating ON/OFF Cancel -900 mbar Yes
- Weight:
- W 375 x D 440 x H 271 mm 15.1 kg

Vacuuming intensity can be regulated Sealing duration can be regulated: 3 - 9 seconds Vacuum pump: 60 L/min. (approx. 4 m^{3 /h)} Sealing rod length: 300 mm Number of sealing seams: 2



A clamp bar in the chamber prevents the vacuuming bag from slipping



Combined vacuuming and sealing

Manual sealing

Marinating





Vacuum packaging machine K 300/60L

Add on Products

