



- |                             |   |                  |                               |
|-----------------------------|---|------------------|-------------------------------|
| • Fitting type:             | Single lever mixer  | • Assembly type: | Single-hole borehole          |
| • Design:                   | Mixer tap with dishwashing shower arm   | • Material:      | Screw system<br>Chrome-plated |
| • Flow at 3 bar:            | Shower arm: 18 L / min.<br>Jet regulator: 40 L / min.   | • Size:          | W 65 x D 450 x H 1,540 mm     |
| • Properties:               | Replaceable sieve<br>Spring mechanism<br>Rubber stopper ring<br>No chrome-damage by additional hard-nickel coating<br>Check valve<br>No recoil thanks to blockable screen-shower head with closing delay<br>Hose can be loaded up to 150 kg, hot water resistant, pressure resistant<br>Stuffing box seals<br>Full metal<br>Water pressure can be regulated with a setting strong | • Weight:        | 8.5 kg                        |
| • Handles:                  | Chrome<br>Thermally insulated   |                  |                               |
| • Installation:             | Copper pipe connection 15 mm  |                  |                               |
| • Jet regulator mouthpiece: | M22   |                  |                               |
| • Swivelling outlet:        | 180°  |                  |                               |
| • Important information:    | -   |                  |                               |
| • Diameter table borehole:  | 42 mm   |                  |                               |
| • Valve type:               | High-performance cartridge with ceramic washer equipment  |                  |                               |