

iVide Plus Sous vide thermal circulator

222997

High precision sous vide thermal circulator with temperature control. 4 inch Touch Screen interface. Designed to fit to any round or flat cooking vessel with a minimum depth of 16.5 cm by means of a clamp. Best performances up to 80 litres. Working temperature 5°C to 99°C, accuracy 0.07°C. Timer can be set between 1 minute and 99 hours. Multiple Machines can be managed from the app. Offers exceptional temperature stability. Low level water protection device switches off the sous vide in case of accidental use without water. Circulating pump to eliminate cold and hot spots. Temperature sensor to prevent overload and overheating. IPX7, can withstand splashes and accidental submersion. App: Precise temperature control from anywhere. A collection of over 600 recipes. Our Sous Vide Calculator: We've done all the testing and research for you, which means no more scouring the internet for information. Recipe Memory: Store your own times and temperatures. Cook history: For greater HACCP control store your last cook 10 times and temperatures. Multi device cooking: Control Several cookers form one app. Notifications to confirm when the water is at temperature, and the food is cooked. Cook time complete, don't worry the app will keep the food at the optimum temperature for holding.



Specifications

| | |
|----------------------|-------------------|
| Usage area | : Kitchen |
| Voltage | : 230 |
| Temp range from [°C] | : 5°C |
| Temp range to [°C] | : 99°C |
| Gradation | : 0.07 |
| Gradation unit | : °C |
| Electrician needed | : No |
| Materials | : Stainless steel |
| Packed per | : 1 |
| Packaging type | : Box |
| Length (mm) | : 130 |
| Width (mm) | : 145 |
| Height (mm) | : 330 |
| Power (input) (W) | : 2200 |
| Programmable | : No |
| Drain tap | : No |
| Measurements | : 130x145x(H)330 |

Transport specifications

| | |
|----------------------------|-----------------|
| EAN | : 8711369222997 |
| Intrastat code | : 84198180 |
| Gross weight (kg) | : 3.9 |
| Net weight (kg) | : 3 |
| Export carton length (mm) | : 395 |
| Export carton width (mm) | : 385 |
| Export carton height (mm) | : 380 |
| Quantity per export carton | : 4 |
| Sales units per pallet | : 96 |
| Plastic packaging (gram) | : 109 |

HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu