

Automatic fill boiler

240717

Made from brushed stainless steel with polypropylene lid and handles. The double walled kettle increases heating efficiency and insulation. When connected to the water mains the boiler will refill automatically. Fitted with two waterlevel sensors. Control panel fitted with digital display and heating and keep warm indicator lights. Temperature can be set from 30°C up to 100°C. With keep warm function, auto power down and overflow prevention sensor. The non-drip tap is made from stainless steel, has a cool touch handle, and is installed so a pot can be placed underneath it. Lid fitted with a twist-lock and cool touch handles. Comes with a removable drip tray. Available in 2 sizes: 240717 – max. capacity 8.5 l, can boil up to 23 l/h. 240724 – max. capacity 17.5 l, can boil up to 33 l/h.

**HENDI B.V.**

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu



HENDI

Tools for Chefs

Specifications

Usage area	: Kitchen
Not intended for	: Chocolate milk, Milk
Voltage	: 230
Temp range from (°C)	: 30°C
Temp range to (°C)	: 100°C
Unit temperature	: Celsius
Heating element	: Heater
Ingress protection	: IPX3
Cord length (mm)	: 1500
Protections	: Thermal cutout, Overheat protection
Materials	: Stainless steel, 18/8 Stainless steel, PP (Polypropylene)

Packed per	: 1
Length (mm)	: 300
Width (mm)	: 285
Height (mm)	: 503
Diameter (mm)	: 220
Weight of item (kg)	: 4.08
Maximum volume (L)	: 11.04
Usable volume (L)	: 8.5
Power (input) (W)	: 2000
Control panel	: Digital
Programmable	: Yes
Drain tap	: Yes
Measurements	: 300x285x(H)503

Transport specifications

EAN	: 8711369240717
Intrastat code	: 84198120
Gross weight (kg)	: 5.45
Net weight (kg)	: 4.13
Sales units per pallet	: 48
Plastic packaging (gram)	: 31

HENDI B.V.

Innovatielaan 6
6745 XW De Klomp, The Netherlands
T: +31 (0)317 681 040
E: info@hendi.eu

HENDI Polska Sp. z o.o.

ul. Firmowa 12
62-023 Robakowo, Poland
T: +48 61 6587000
E: info@hendi.pl

HENDI GmbH

Ehring 15
5112 Lamprechtshausen, Austria
T: +43 (0) 6274 200 10 0
E: office.austria@hendi.eu

HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14
Braşov, 500164, Romania
T: +40 268 320330
E: office@hendi.ro

PKS HENDI South East Europe SA

5 Metsovou Str.
18346 Moschato, Athens, Greece
T: +30 210 4839700
E: info@pks-hendi.com

HENDI Italia S.R.L.

Via Leonardo da Vinci 4
39100 Bolzano (BZ), Italy
T: 800 727 438
E: office.italy@hendi.eu