# KERN 440-33N

The classic balance in the laboratory





Measuring system				
Adjustment options:	External calibration			
Linearity:	20 mg			
Readability [d]:	10 mg			
Recommended adjusting weight:	200 g (M1)			
Repeatability:	10 mg			
Resolution:	20000			
Stabilisation time under laboratory conditions:	3 s			
Warm up time:	30 min			
Weighing capacity [Max]:	200 g			
Weighing system:	Strain gauge			
Weighing units:	kg ozt tl (HK) tol g mo lb dwt ct oz tl (Tw) gn			

Display digit height (large):	1,500 cm
Counting	
Counting resolution:	10000
Mininum piece weight at piece counting (Laboratory:	20 mg
Mininum piece weight at piece counting (Normal):	200 mg

Display

Functions	
Counting function:	yes
Percentage determination:	yes
Vibration-free weighing (Animal weighing program):	yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C

Power supply				
Battery:	9 V Block			
Charging time:	10 h			
Input voltage:	100-240V AC 50/60Hz 0.5A			
Mains adapter/adapter included:	EURO CH US UK			
Operating time:	20 h			
Operating time (Backlight off):	20 h			
Rechargeable battery:	Rchrg. battery optional			

## Service

Adjustment at the location of installation: 961-247

DAkkS Certificate: 963-127

Category	
Brand:	KERN
Category:	Balances
Product Group:	Precision balance

Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	165 x 230 x 82 mm
Material weighing plate:	stainless steel
Weighing space (WxDxH):	100 x 200 x 100 mm
Weighing surface (d):	105

## Piktogramme

#### STANDARD

OT/ (ND/ (TD								
i i	· ARA •	GLP	**	<b>△</b> A	%	2	<b>^</b> -	Ę
CAL EXT	RS 232	PRINTER	PCS	RECIPE	PERCENT	UNIT	MOVE	UNDER
BATT	MULTI	DMS	1 DAY					

#### **OPTION**

