

# KERN 572-35

All-rounder e.g. as precision balance in the laboratory or in harsh industrial applications



## Functions

Conversion function:	yes
Counting function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Suspended weighing:	Loop
Vibration-free weighing (Animal weighing program):	yes

## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	10 °C

## Power supply

Charging time:	10 h
Input voltage:	100 V - 240 V
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH US UK
Operating time (Backlight off):	30 h
Operating time (Backlight on):	15 h
Rechargeable battery:	Rchrg. battery optional

## Service

DAkkS Certificate:	963-127
--------------------	---------

## Category

Brand:	KERN
Category:	Balances
Product Group:	Precision balance

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	400 x 340 x 220 mm
Gross weight:	4,100 kg
Net weight:	2,300 kg
Shipping method:	Parcel service

## Construction

Casing material:	Cast aluminium alloys
Dimensions housing (WxDxH):	180 x 310 x 85 mm
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	180 x 310 x 90 mm
Weighing surface (d):	150

## Measuring system

Adjustment options:	External calibration
Linearity:	30 mg
Readability [d]:	10 mg
Recommended adjusting weight:	2 kg (F1)
Repeatability:	10 mg
Resolution:	240000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	2 h
Weighing capacity [Max]:	2,400 kg
Weighing system:	Strain gauge
Weighing units:	t kg to tl (HK) g mo tl (Cn) lb tl (Singap. Malays) dwt ct oz tl (Tw) gn

## Display

Display digit height (large):	1,800 cm
-------------------------------	----------

## Counting

Counting resolution:	240000
Minimum piece weight at piece counting (Laboratory):	10 mg
Minimum piece weight at piece counting (Normal):	100 mg

# KERN 572-35

All-rounder e.g. as precision balance in the laboratory or in harsh industrial applications



## Piktogramme

### STANDARD



### OPTION

