KERN ACS100-4



The bestseller in analytical balances, with high-quality single-cell weighing system, also with EC type approval [M]



Measuring system

Adjustment options:	External calibration		
Linearity:	0,300 mg		
Minimum weight (USP):	400 mg		
Readability [d]:	0,100 mg		
Recommended adjusting weight:	100 g (E2)		
Repeatability:	0,200 mg		
Resolution:	1.200.000		
Stabilisation time under laboratory conditions:	3 s		
Warm up time:	8 h		
Weighing capacity [Max]:	120 g		
Weighing units:	mg g ct		

Display

Display digit height (large):

Counting	
Counting resolution:	120000
Mininum piece weight at piece counting (Laboratory:	1 mg
Mininum piece weight at piece counting (Normal):	10 mg

1,400 cm

Reference weight:	yes			
Functions				
Counting function:	yes			
Function to save totals:	yes			
Percentage determination:	yes			
Standby function:	yes			
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	85 %			
Maximum operating temperature:	30 °C			
Minimum ambient temperature:	10 °C			
Minimum humidity:	20 %			
Power supply				
Input voltage:	110 V - 230 V AC			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	US EURO CH UK			
Service				
DAkkS Certificate:	963-101			
Category				
Brand:	KERN			
Category:	Balances			
Category: Product Group:				
• .	Balances			
Product Group:	Balances			
Product Group: Packaging & shipping	Balances Analytical balance			
Product Group: Packaging & shipping Delivery:	Balances Analytical balance 24 h			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Balances Analytical balance 24 h 392 x 570 x 520 mm			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Balances Analytical balance 24 h 392 x 570 x 520 mm 8,491 kg			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	Balances Analytical balance 24 h 392 x 570 x 520 mm 8,491 kg 5,746 kg			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	Balances Analytical balance 24 h 392 x 570 x 520 mm 8,491 kg 5,746 kg			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	Balances Analytical balance 24 h 392 x 570 x 520 mm 8,491 kg 5,746 kg Parcel service			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material:	Balances Analytical balance 24 h 392 x 570 x 520 mm 8,491 kg 5,746 kg Parcel service Plastic			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions draft shield (WxDxH):	Balances Analytical balance 24 h 392 x 570 x 520 mm 8,491 kg 5,746 kg Parcel service Plastic 201 x 220 x 256 mm			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions draft shield (WxDxH): Dimensions housing (WxDxH):	Balances Analytical balance 24 h 392 x 570 x 520 mm 8,491 kg 5,746 kg Parcel service Plastic 201 x 220 x 256 mm 210 x 345 x 328 mm			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions draft shield (WxDxH): Dimensions housing (WxDxH): Level indicator:	Balances Analytical balance 24 h 392 x 570 x 520 mm 8,491 kg 5,746 kg Parcel service Plastic 201 x 220 x 256 mm 210 x 345 x 328 mm yes			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions draft shield (WxDxH): Dimensions housing (WxDxH): Level indicator: Material weighing plate:	Balances Analytical balance 24 h 392 x 570 x 520 mm 8,491 kg 5,746 kg Parcel service Plastic 201 x 220 x 256 mm 210 x 345 x 328 mm yes stainless steel			
Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions draft shield (WxDxH): Dimensions housing (WxDxH): Level indicator: Material weighing plate: Revolving screw feet:	Balances Analytical balance 24 h 392 x 570 x 520 mm 8,491 kg 5,746 kg Parcel service Plastic 201 x 220 x 256 mm 210 x 345 x 328 mm yes stainless steel yes			

KERN ACS100-4



The bestseller in analytical balances, with high-quality single-cell weighing system, also with EC type approval [M]

Piktogramme

STANDARD

MULTI SC TECH 1 DAY

Ť.	CAL EXT	•	GLP		\	%	-√+ ⊙	3
CAL INT	CAL EXT	USB	PRINTER	PCS	RECIPE	PERCENT	TOL	UNIT
B	मि							

OPTION



FACTORY

