KERN BFA1T-4SNM



Weighing bridge with screw-on weighing plate (IP67) and stainless steel display device (IP65), with EC type approval [M]



Measuring system	
Adjustment options:	External calibration
Linearity:	1,500 kg
Load cell connection:	6-wire
Number of weighing ranges:	1
Readability [d]:	500 g
Recommended adjusting weight:	1500 kg (M2)
Repeatability:	500 g
Resolution:	3000
Stabilisation time under laboratory conditions:	2 \$
Tare range:	-1,500 t
Warm up time:	10 min
Weighing capacity [Max]:	1,500 t
Weighing system:	Strain gauge
Weighing units:	kg

Display		
Display digit height (large):	5,200 cm	

Technical data about verification	
Minimum load [Min]:	10 kg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	500 g

Functions		
Counting function:	yes	
Function to save totals:	yes	
Vibration-free weighing (Animal weighing program):	yes	

Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Battery:	no battery
Charging time:	12 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	US EURO CH UK
Operating time (Backlight off):	35 h
Operating time (Backlight on):	20 h

Service	
Adjustment at the location of installation	:961-250
DAkkS Certificate:	963-130
Verification:	965-230

Category	
Brand:	KERN
Category:	Balances
Product Group:	Floor scale

Packaging & shipping	
Delivery:	120 h
Dimensions packaging (WxDxH):	1110 x 1070 x 365 mm
Gross weight:	126 kg
Net weight:	97 kg
Shipping method:	Freight forwarder
UN number:	2800

Construction	
Cable length of display device:	5 m
Dimensions housing (WxDxH):	266 x 165 x 96 mm
Dimensions of display device (WxDxH):	266 x 165 x 96 mm
Dimensions of weighing plate (WxDxH):	1000 x 1000 x 95 mm
Level indicator:	yes
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	1000 x 1000 mm

KERN BFA1T-4SNM



Weighing bridge with screw-on weighing plate (IP67) and stainless steel display device (IP65), with EC type approval [M]

Piktogramme STANDARD LALEXT PCS SUM TOL MOVE IP 65 IP 67 MULTI DMS CALEXT PCS SUM TOL MOVE IP 65 IP 67 MULTI DMS OPTION DAKKS +3 DAYS FACTORY

RS 232 ACCU +3 DAYS