
KERN BID1T-4LM



Floor scale with EC type approval [M] and the best price-performance ratio - now also as a high-resolution dual-range balance



Measuring system	
Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	1,500 kg
Load cell connection:	4-wire
Number of weighing ranges:	1
Readability [d]:	500 g
Recommended adjusting weight:	1500 kg (M2)
Repeatability:	500 g
Resolution:	3000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-1,500 t
Warm up time:	10 min
Weighing capacity [Max]:	1,500 t
Weighing system:	Strain gauge
Weighing units:	kg PCS g lb tJ HJ oz
Display	
Display digit height (large):	2,500 cm
Display digit height (small):	2,500 cm

Technical data about verification

Minimum load [Min]:	10 kg	
Periodic Verification for Italy:	969-112	
Verification approval conforming to 2014/31/EU:	yes	
Verification by KERN possible:	yes	
Verification class:	III	
Verification value [e]:	500 g	

Functions	
Counting function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %
Power supply	
Battery:	no battery
Charging time:	3 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	US EURO CH AUS UK
Operating time:	100 h
Operating time (Backlight off):	43 h
Operating time (Backlight on):	26 h
Rechargeable battery:	Rchrg. battery optional - intern
Service	
Adjustment at the location of installation	961-250
DAkkS Certificate:	963-130
Verification:	965-230
Category	
Brand:	KERN
Category:	Balances
Product Group:	Floor scale
Packaging & shipping	
Delivery:	48 h
Dimensions packaging (WxDxH):	1550 x 1550 x 265 mm
Gross weight:	180 kg
Net weight:	155 kg
Shipping method:	Freight forwarder
Construction	
Cable length:	5 m
Cable length of display device:	5 m
Dimensions of display device	268 x 115 x 80 mm
(WxDxH):	4

1

KERN BID1T-4LM



Floor scale with EC type approval [M] and the best price-performance ratio - now also as a high-resolution dual-range balance

Dimensions of weighing plate (WxDxH):	1500 x 1500 x 108 mm		
Level indicator:	yes		
Revolving screw feet:	yes		
Wall mount:	yes		
Weighing surface (WxD):	1500 x 1500 mm		

Piktogramme

STANDARD

	• 6660 •	KCP	GLP			<u>%</u>	-√+ ⊙ 🤊 ୬	
CAL EXT	RS 232	PROTOCOL	PRINTER	PCS	SUM	PERCENT	TOL	MOVE
665	000		DMS	2 DAYS				

FACTORY

•	*	?	문	Μ
USB	BT 4.0	WIFE	LAN	+3 DAYS