
KERN CCS300K0.01







Measuring system	
Adjustment options:	External calibration
Linearity:	50 mg
Recommended adjusting weight:	300 kg (M1)
Repeatability:	20 mg
Stabilisation time under laboratory conditions:	2 s
Weighing system:	Strain gauge
Weighing units:	kg lb

Display digit height (large):	2 cm
Counting	
Counting resolution:	6000000
Mininum piece weight at piece counting (Laboratory:	50 mg
Mininum piece weight at piece	500 mg

Display

counting (Normal):

Reference weight:

Functions		
Conversion function:	yes	
Counting function:	yes	
Function to save totals:	yes	
PRE-TARE function:	yes	
Weighing with tolerance range:	yes	

yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0°C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH US UK
Operating time (Backlight off):	60 h
Operating time (Backlight on):	70 h
Rechargeable battery:	Rchrg. battery optional

CIVICC		

Adjustment at the location of installation: abhängig von

Auflösung/Max | depends on resolution and capacity

DAkkS Certificate: 962-129-127

Category

Brand: **KERN**

Product Group: Counting system

Packaging & shipping

Delivery: 72 h

Dimensions packaging (WxDxH): 670 x 1045 x 545 mm

Gross weight: 29,400 kg Net weight: 23,700 kg Shipping method: Parcel service

Construction

1,500 m Cable length: Cable length of display device: 5 m Casing material: **Plastic** 650 x 500 x 142 mm Dimensions of weighing plate (WxDxH): Level indicator: yes Material weighing plate: stainless steel Revolving screw feet: yes 650 x 500 mm Weighing surface (WxD):

Piktogramme

STANDARD



OPTION

