
KERN CCS300K0.1







Measuring system	
Adjustment options:	External calibration
Linearity:	200 mg
Recommended adjusting weight:	300 kg (M1)
Repeatability:	100 mg
Stabilisation time under laboratory conditions:	2 s
Weighing system:	Strain gauge
Weighing units:	kg lb

Counting	
Counting resolution:	3000000
Mininum piece weight at piece counting (Laboratory:	100 mg
Mininum piece weight at piece counting (Normal):	1 g
Reference weight:	yes

2 cm

Display

Display digit height (large):

Functions		
Conversion function:	yes	
Counting function:	yes	
Function to save totals:	yes	
PRE-TARE function:	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0°C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH US UK
Operating time (Backlight off):	60 h
Operating time (Backlight on):	70 h
Rechargeable battery:	Rchrg. battery optional

Service
Adjustment at the location of installation; abbängig ve

Adjustment at the location of installation: abhängig von

Auflösung/Max | depends on resolution and capacity

DAkkS Certificate: 962-129-128

Cate	egory		

Brand: **KERN**

Product Group: Counting system

Packaging & shipping	
Delivery:	72 h
Dimensions packaging (WxDxH):	670 x 1045

x 545 mm Gross weight: 29,400 kg Net weight: 23,700 kg Shipping method: Parcel service

Construction	
Cable length:	1,500 m
Cable length of display device:	5 m
Casing material:	Plastic
Dimensions of weighing plate (WxDxH):	650 x 500 x 142 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes

Piktogramme

Weighing surface (WxD):

STANDARD



650 x 500 mm

OPTION

