
KERN CCS30K0.01.





on resolution and capacity



Measuring system	
Adjustment options:	External calibration
Linearity:	30 mg
Recommended adjusting weight:	30000 g (M1)
Repeatability:	20 mg
Stabilisation time under laboratory conditions:	2 s
Weighing system:	Strain gauge
Weighing units:	kg lb

Display digit height (large):	2 cm
Counting	
Counting resolution:	600000
Mininum piece weight at piece counting (Laboratory:	50 mg
Mininum piece weight at piece	500 mg

Display

counting (Normal): Reference weight:

Weighing with tolerance range:

Functions		
Conversion function:	yes	
Counting function:	yes	
Function to save totals:	yes	
PRE-TARE function:	yes	

yes

yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0°C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	US EURO CH UK
Operating time (Backlight off):	60 h
Operating time (Backlight on):	70 h
Rechargeable battery:	Rchrg. battery optional

Adjustment at the location of installation: abhängig vor

Service

Auflösung/Max | depends

DAkkS Certificate: 962-128-127

Category **KERN** Brand:


Product Group: Counting system

Packaging & shipping 48 h Delivery: Dimensions packaging (WxDxH): 940 x 640 x 230 mm Gross weight: 15,900 kg Net weight: 12,050 kg Shipping method: Parcel service

Construction	
Cable length:	1,500 m
Cable length of display device:	5 m
Casing material:	Plastic
Dimensions of weighing plate (WxDxH):	400 x 300 x 128 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	320 x 330 x 125 mm
Revolving screw feet:	yes
Weighing surface (WxD):	400 x 300 mm

Piktogramme

STANDARD



OPTION



4 DAYS 5 DAYS