## **KERN CCS3T-1**







Measuring system	
Adjustment options:	External calibration
Linearity:	500 mg
Recommended adjusting weight:	3000 kg (M1)
Repeatability:	200 mg
Stabilisation time under laboratory conditions:	2 s
Weighing system:	Strain gauge
Weighing units:	kg lb

Counting		i
Counting resolution:	30000000	
Mininum piece weight at piece counting (Laboratory:	100 mg	
Mininum piece weight at piece counting (Normal):	1 g	
Reference weight:	yes	

2 cm

Display

Display digit height (large):

Functions		
Conversion function:	yes	
Counting function:	yes	
Function to save totals:	yes	
PRE-TARE function:	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0°C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH UK US
Operating time (Backlight off):	60 h
Operating time (Backlight on):	70 h
Rechargeable battery:	Rchrg. battery optional

Adjustment at the location of installation:	ab	hängig	vor
		e1 ···	/B 4

Service

Auflösung/Max | depends on resolution and capacity

DAkkS Certificate: 962-132-128

Category **KERN** Brand:

Product Group: Counting system

Packaging & shipping 96 h Delivery: Dimensions packaging (WxDxH): 1550 x 1300 x 545 mm Gross weight: 185 kg Net weight: 180 kg Freight forwarder Shipping method:

Construction	
Cable length:	1,500 m
Cable length of display device:	5 m
Casing material:	Plastic
Dimensions of weighing plate (WxDxH):	1500 x 1250 x 80 mm
Level indicator:	yes
Material weighing plate:	Metal lacquered
Revolving screw feet:	yes
Weighing surface (WxD):	1500 x 1250 mm

## Piktogramme

## STANDARD



## **OPTION**

