## KERN CCS600K-2U



Counting system to count the smallest parts in the largest quantities, counting resolution up to 999,999 points



External calibration
50 mg
600 kg (M1)
20 mg
2 s
Strain gauge
kg lb

Display

Display digit height (large):

Counting	
Counting resolution:	12000000
Mininum piece weight at piece counting (Laboratory:	50 mg
Mininum piece weight at piece counting (Normal):	500 mg
Reference weight:	yes

2 cm

Functions		
Conversion function:	yes	
Counting function:	yes	
Function to save totals:	yes	
PRE-TARE function:	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH UK US
Operating time (Backlight off):	60 h
Operating time (Backlight on):	70 h
Rechargeable battery:	Rchrg. battery optional

Service	
Adjustment at the location of installation: abhängig	٧n

angig von

Auflösung/Max | depends on resolution and capacity

DAkkS Certificate: 962-130-127

Cate	egory		
_			

Brand: **KERN** 

Product Group: Counting system

# Packaging & shipping

96 h Delivery:

Dimensions packaging (WxDxH): 860 x 130 x 500 mm

Gross weight: 50 kg Net weight: 46 kg

Shipping method: Freight forwarder

## Construction

1,500 m Cable length: Cable length of display device: 5 m Casing material: **Plastic** 840 x 1190 x 90 mm Dimensions of weighing plate (WxDxH): Level indicator: yes Material weighing plate: Metal lacquered Revolving screw feet: yes Weighing surface (WxD): 840 x 1190 mm

## Piktogramme

#### STANDARD



#### OPTION

