KERN CCS60K0.1.







Measuring system	
Adjustment options:	External calibration
Linearity:	200 mg
Recommended adjusting weight:	50000 g (M1)
Repeatability:	100 mg
Stabilisation time under laboratory conditions:	2 s
Weighing system:	Strain gauge
Weighing units:	kg lb

1 7 0 0 0 0 7	
Counting	
Counting resolution:	600000
Mininum piece weight at piece counting (Laboratory:	100 mg
Mininum piece weight at piece counting (Normal):	1 g

2 cm

yes

Display

Display digit height (large):

Reference weight:

Functions		
Conversion function:	yes	
Counting function:	yes	
Function to save totals:	yes	
PRE-TARE function:	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0°C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	US EURO CH UK
Operating time (Backlight off):	60 h
Operating time (Backlight on):	70 h
Rechargeable battery:	Rchrg. battery optional

Service
Adjustment at the location of installation: abhängig von

Auflösung/Max | depends on resolution and capacity

DAkkS Certificate: 962-129-128

Cat	egory		
_			

Brand: KERN

Product Group: Counting system

Packaging & shipping

Delivery: 48 h

Dimensions packaging (WxDxH): 935 x 650 x 230 mm


Gross weight: 17 kg
Net weight: 12,300 kg
Shipping method: Parcel service

Construction

1,500 m Cable length: Cable length of display device: 5 m Casing material: **Plastic** Dimensions of weighing plate 400 x 300 x 128 mm (WxDxH): Level indicator: yes Material weighing plate: stainless steel Overall dimensions mounted 320 x 330 x 125 mm (WxDxH): Revolving screw feet: yes Weighing surface (WxD): 400 x 300 mm

Piktogramme

STANDARD





4 DAYS 5 DAYS

