KERN CKE36K0.1-2020e



Easy to use, self-explanatory counting scale with laboratory accuracy, counting resolution up to 360,000 points - now also with KERN KCP and stronger battery operation



| Measuring system | | | |
|---|--|--|--|
| Adjustment options: | External calibration | | |
| Linearity: | 300 mg | | |
| Readability [d]: | 100 mg | | |
| Recommended adjusting weight: | 36 kg (E2) | | |
| Repeatability: | 100 mg | | |
| Resolution: | 360000 | | |
| Stabilisation time under laboratory conditions: | 3 s | | |
| Tare range: | 36 kg | | |
| Warm up time: | 2 h | | |
| Weighing capacity [Max]: | 36 kg | | |
| Weighing system: | Strain gauge | | |
| Weighing units: | custom factor dwt oz gn kg PCS ozt g lb | | |
| Display | | | |
| Display digit height: | 2,500 cm | | |
| Counting | | | |
| Counting resolution: | 360000 | | |

| Counting resolution: | 360000 | |
|---|------------|--|
| Mininum piece weight at piece counting (Laboratory: | 100 mg | |
| Mininum piece weight at piece counting (Normal): | 1 g | |
| Reference weight: | yes | |
| | | |
| Functions | | |
| Functions Counting function: | yes | |
| - | yes yes | |
| Counting function: | | |

| Environmental conditions | | | | |
|---------------------------------|-------------------------------------|--|--|--|
| Maximum humidity: | 80 % | | | |
| Maximum operating temperature: | 40 °C | | | |
| Minimum ambient temperature: | 10 °C | | | |
| Power supply | | | | |
| Battery: | 6x1.5 V AAA | | | |
| Charging time: | 10 h | | | |
| Input voltage: | 110 V - 240 V AC | | | |
| Mains adapter: | Mains adapter external | | | |
| Mains adapter/adapter included: | EURO CH UK US | | | |
| Operating time: | 80 h | | | |
| Operating time (Backlight off): | 90 h | | | |
| Operating time (Backlight on): | 40 h | | | |
| Rechargeable battery: | Rchrg. battery optional - intern | | | |
| Service | | | | |
| DAkkS Certificate: | 963-128 | | | |
| Category | | | | |
| Brand: | KERN | | | |
| Category: | Balances | | | |
| Product Group: | Counting scale | | | |
| Packaging & shipping | | | | |
| Delivery: | 24 h | | | |
| Dimensions packaging (WxDxH): | 470 x 470 x 190 mm | | | |
| Gross weight: | 7,600 kg | | | |
| Net weight: | 6,500 kg | | | |
| Shipping method: | Parcel service | | | |
| Construction | | | | |
| Dimensions housing (WxDxH): | 350 x 390 x 120 mm | | | |
| Level indicator: | yes | | | |
| Material weighing plate: | stainless steel | | | |
| Revolving screw feet: | yes | | | |
| Weighing surface (WxD): | 340 x 240 mm | | | |

KERN CKE36K0.1-2020e



Easy to use, self-explanatory counting scale with laboratory accuracy, counting resolution up to 360,000 points - now also with KERN KCP and stronger battery operation

Piktogramme

STANDARD

| CAL EXT | | KCP Protocol | PCS | -√+ ⊙ 🤊 TOL | BATT | B H |
|---------|-----|-----------------|-----|-------------------|------|-----|
| UNDER | DMS | 1 DAY | | | | |

OPTION



FACTORY

