KERN ECB10K-3N

Plain, mobile, uncomplicated





| Measuring system | |
|---|----------------------|
| Adjustment options: | External calibration |
| Linearity: | 20 g |
| Readability [d]: | 5 g |
| Recommended adjusting weight: | 5 kg (M3) |
| Repeatability: | 5 g |
| Resolution: | 2000 |
| Stabilisation time under laboratory conditions: | 2\$ |
| Tare range: | 10 kg |
| Warm up time: | 10 min |
| Weighing capacity [Max]: | 10 kg |
| Weighing system: | Strain gauge |
| Weighing units: | kg |

| 2,100 cm |
|----------|
| |

| Environmental conditions | |
|--------------------------------|-------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 35 °C |
| Minimum ambient temperature: | 5°C |

| Power supply | |
|---------------------------------|----------------------------------|
| Battery: | 6x1.5 V AA |
| Charging time: | 10 h |
| Input voltage: | 220 V - 240 V AC 50 Hz |
| Mains adapter: | Mains adapter external |
| Operating time: | 100 h |
| Operating time (Backlight off): | 30 h |
| Operating time (Backlight on): | 30 h |
| Rechargeable battery: | Rchrg. battery optional - intern |

Service

Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

| Category | |
|----------------|-------------|
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Bench scale |

| 24 h |
|-------------------|
| 380 x 405 x 90 mm |
| 2,880 kg |
| 2,500 kg |
| Parcel service |
| |

| Construction | |
|---------------------------------------|-------------------|
| Casing material: | Plastic |
| Dimensions housing (WxDxH): | 320 x 300 x 60 mm |
| Dimensions of weighing plate (WxDxH): | 320 x 260 x 60 mm |
| Material weighing plate: | stainless steel |
| Weighing surface (WxD): | 320 x 260 mm |

Piktogramme

STANDARD









OPTION





