# KERN EOC100K-3L



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use



## Measuring system

Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	6 g   15 g
Load cell connection:	4-wire
Readability [d]:	2 g   5 g
Recommended adjusting weight:	150 kg (F2)
Repeatability:	2 g   5 g
Resolution:	30 30.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-150 kg
Warm up time:	2 h   2 h
Weighing capacity [Max]:	60 kg   150 kg
Weighing system:	Strain gauge
Weighing units:	kg PCS g lb oz

## Display

Display digit height (large):	2,500 cm
Display digit height (small):	2,500 cm

### Counting

Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	5 g
Mininum piece weight at piece counting (Normal):	50 g

#### Functions

Counting function:	yes
Percentage determination:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

Environmental conditions					
Maximum humidity:	80 %				
Maximum operating temperature:	40 °C				
Minimum ambient temperature:	-10 °C				
Minimum humidity:	0 %				
Power supply					
Charging time:	3 h				
Input voltage:	100V-240V 0.4A				
Mains adapter:	Mains adapter external				
Mains adapter/adapter included:	EURO CH UK US				
Operating time:	100 h				
Operating time (Backlight off):	43 h				
Operating time (Backlight on):	26 h				
Rechargeable battery:	Rchrg. battery optional -				
	intern				
Service					
Adjustment at the location of installation	n:961-249				
DAkkS Certificate:	963-129				
Category					
	KERN				
Brand:	KERN				
Brand: Category:	KERN Balances				
Category:	Balances				
Category: Product Group:	Balances				
Category: Product Group: Packaging & shipping	Balances Industiral scale				
Category: Product Group: Packaging & shipping Delivery:	Balances Industiral scale 24 h				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Balances Industiral scale 24 h 985 x 625 x 185 mm				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Balances Industiral scale 24 h 985 x 625 x 185 mm 12,500 kg				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	Balances Industiral scale 24 h 985 x 625 x 185 mm 12,500 kg 9 kg				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	Balances Industiral scale 24 h 985 x 625 x 185 mm 12,500 kg 9 kg				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device:	Balances Industiral scale 24 h 985 x 625 x 185 mm 12,500 kg 9 kg Parcel service				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	Balances Industiral scale 24 h 985 x 625 x 185 mm 12,500 kg 9 kg Parcel service 3 m				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate	Balances Industiral scale 24 h 985 x 625 x 185 mm 12,500 kg 9 kg Parcel service 3 m				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	Balances Industiral scale 24 h 985 x 625 x 185 mm 12,500 kg 9 kg Parcel service 3 m 268 x 115 x 80 mm 500 x 400 x 120 mm				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand:	Balances Industiral scale 24 h 985 x 625 x 185 mm 12,500 kg 9 kg Parcel service 3 m 268 x 115 x 80 mm				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator:	Balances   Industiral scale   24 h   985 x 625 x 185 mm   12,500 kg   9 kg   Parcel service   3 m   268 x 115 x 80 mm   500 x 400 x 120 mm   33 cm   yes				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate:	Balances   Industiral scale   24 h   985 x 625 x 185 mm   12,500 kg   9 kg   Parcel service   3 m   268 x 115 x 80 mm   500 x 400 x 120 mm   33 cm				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate: Revolving screw feet:	Balances   Industiral scale   24 h   985 x 625 x 185 mm   12,500 kg   9 kg   Parcel service   3 m   268 x 115 x 80 mm   500 x 400 x 120 mm   33 cm   yes				
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate:	Balances   Industiral scale   24 h   985 x 625 x 185 mm   12,500 kg   9 kg   Parcel service   3 m   268 x 115 x 80 mm   500 x 400 x 120 mm   33 cm   yes   stainless steel				

## KERN EOC100K-3L



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use

#### Piktogramme

#### STANDARD

	- 888	KCP	GLP			%	-√+ ⊙ 🤊	^
CAL EXT	RS 232	PROTOCOL	PRINTER	PCS	SUM	PERCENT	TOL	MOVE
•••	B							
IP 65	MULTI	DMS	1 DAY					

### OPTION

<b></b> )	DAkkS
ACCU	+3 DAYS