KERN EOC 20K-3A



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use



Measuring system

e ,			
Adjustment options:	External calibration		
Linearisation (points):	3		
Linearity:	6 g		
Load cell connection:	4-wire		
Readability [d]:	2 g		
Recommended adjusting weight:	24 kg (M1)		
Repeatability:	2 g		
Resolution:	12000		
Stabilisation time under laboratory conditions:	2s		
Tare range:	-24 kg		
Warm up time:	30 min		
Weighing capacity [Max]:	24 kg		
Weighing system:	Strain gauge		
Weighing units:	kg PCS g lb oz		

Display

Display digit height (large):	2,500 cm
Display digit height (small):	2,500 cm

Counting

Counting resolution:	24000
Mininum piece weight at piece counting (Laboratory:	1 g
Mininum piece weight at piece counting (Normal):	10 g

Functions

Counting function:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0 %			
Power supply				
Charging time:	3 h			
Input voltage:	100V-240V 0.4A			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	EURO CH UK US			
Operating time:	100 h			
Operating time (Backlight off):	43 h			
Operating time (Backlight on):	26 h			
Rechargeable battery:	Rchrg. battery optional - intern			
Service				
Adjustment at the location of installation	n:961-248			
DAkkS Certificate:	963-128			
Category				
Brand:	KERN			
Category:	KERN Balances			
Category:	Balances			
Category: Product Group:	Balances			
Category: Product Group: Packaging & shipping	Balances Industiral scale			
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Balances Industiral scale 24 h 715 x 360 x 185 mm 7,500 kg			
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	Balances Industiral scale 24 h 715 x 360 x 185 mm			
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Balances Industiral scale 24 h 715 x 360 x 185 mm 7,500 kg			
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	Balances Industiral scale 24 h 715 x 360 x 185 mm 7,500 kg 5,200 kg			
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	Balances Industiral scale 24 h 715 x 360 x 185 mm 7,500 kg 5,200 kg			
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	Balances Industiral scale 24 h 715 x 360 x 185 mm 7,500 kg 5,200 kg Parcel service			
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	Balances Industiral scale 24 h 715 x 360 x 185 mm 7,500 kg 5,200 kg Parcel service 3 m			
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate	Balances Industiral scale 24 h 715 x 360 x 185 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm			
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	Balances Industiral scale 24 h 715 x 360 x 185 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm			
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand:	Balances Industiral scale 24 h 715 x 360 x 185 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm			
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator:	Balances Industiral scale 24 h 715 x 360 x 185 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes			
Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate:	Balances Industiral scale 24 h 715 x 360 x 185 mm 7,500 kg 5,200 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes stainless steel			

KERN EOC 20K-3A



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD

	• 888.•	KCP	GLP		%	+ ③ ③)	^-
CAL EXT	RS 232	PROTOCOL	PRINTER	PCS	PERCENT		MOVE
666	B						
IP 65	MULTI	DMS	1 DAY				

OPTION

)	DAkkS
ACCU	+3 DAYS