KERN EOC6K-4A



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use



Measuring system

Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	1,500 g
Load cell connection:	4-wire
Readability [d]:	500 mg
Recommended adjusting weight:	6 kg (M1)
Repeatability:	500 mg
Resolution:	12000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-6 kg
Warm up time:	30 min
Weighing capacity [Max]:	6 kg
Weighing system:	Strain gauge
Weighing units:	kg PCS g lb oz

Display

Display digit height (large):	2,500 cm
Display digit height (small):	2,500 cm

Counting

Counting resolution:	24000
Mininum piece weight at piece counting (Laboratory:	250 mg
Mininum piece weight at piece counting (Normal):	2,500 g

Functions

Counting function:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0 %			
Power supply				
Charging time:	3 h			
Input voltage:	100V-240V 0.4A			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	EURO CH UK US			
Operating time:	100 h			
Operating time (Backlight off):	43 h			
Operating time (Backlight on):	26 h			
Rechargeable battery:	Rchrg. battery optional - intern			
Service				
Adjustment at the location of installatio	n:961-248			
DAkkS Certificate:	963-128			
Category				
Brand:	KERN			
Category:	Balances			
Product Group: Industiral scale				
Packaging & shipping				
Delivery:	24 h			
Dimensions packaging (WxDxH):	560 x 400 x 160 mm			
Gross weight:	7,500 kg			
Net weight:	5,200 kg			
	5,200 Kg			
Shipping method:	Parcel service			
Shipping method: Construction	•			
	•			
Construction	Parcel service			
Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	Parcel service 3 m			
Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate	Parcel service 3 m 268 x 115 x 80 mm			
Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm			
Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand:	Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm			
Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator:	Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes			
Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate:	Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes stainless steel			

KERN EOC6K-4A



Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use

Piktogramme

STANDARD

	• 888. •	KCP	GLP		%	-√+ ⊙ 🤊)	^
CAL EXT	RS 232	PROTOCOL	PRINTER	PCS	PERCENT		MOVE
666	B						
IP 65	MULTI	DMS	1 DAY				

OPTION

	DAkkS
ACCU	+3 DAYS