

KERN FCE15K5N

Entry-level bench scale à mobile, practical, lightweight

KERN®



Measuring system

| | |
|---|----------------------|
| Adjustment options: | External calibration |
| Linearity: | 15 g |
| Readability [d]: | 5 g |
| Recommended adjusting weight: | 15 kg (M2) |
| Repeatability: | 10 g |
| Resolution: | 3000 |
| Stabilisation time under laboratory conditions: | 3 s |
| Warm up time: | 10 min |
| Weighing capacity [Max]: | 15 kg |
| Weighing system: | Strain gauge |
| Weighing units: | g |

Display

| | |
|-------------------------------|----------|
| Display digit height (large): | 2,500 cm |
|-------------------------------|----------|

Environmental conditions

| | |
|--------------------------------|-------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 35 °C |
| Minimum ambient temperature: | 5 °C |

Power supply

| | |
|---------------------------------|-------------------------|
| Battery: | 9 V Block |
| Charging time: | 10 h |
| Input voltage: | 220 V - 240 V AC 50 Hz |
| Mains adapter: | Mains adapter external |
| Mains adapter/adaptor included: | US EURO CH UK |
| Operating time: | 12 h |
| Operating time (Backlight off): | 20 h |
| Rechargeable battery: | Rchrg. battery optional |

Service

Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

Category

| | |
|----------------|-------------|
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Bench scale |

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 400 x 330 x 180 mm |
| Gross weight: | 2,850 kg |
| Net weight: | 2,300 kg |
| Shipping method: | Parcel service |

Construction

| | |
|---------------------------------------|---------------------|
| Casing material: | Plastic |
| Dimensions housing (WxDxH): | 270 x 323 x 110 mm |
| Dimensions of weighing plate (WxDxH): | 252 x 228 x 12,5 mm |
| Material weighing plate: | Plastic |
| Weighing surface (WxD): | 252 x 228 mm |

Piktogramme

STANDARD



OPTION

