

KERN FCE6K2N

Entry-level bench scale à mobile, practical, lightweight

KERN®



Measuring system

Adjustment options:	External calibration
Linearity:	4 g
Readability [d]:	2 g
Recommended adjusting weight:	6 kg (M2)
Repeatability:	2 g
Resolution:	3000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	10 min
Weighing capacity [Max]:	6 kg
Weighing system:	Strain gauge
Weighing units:	g

Display

Display digit height (large):	2,500 cm
-------------------------------	----------

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply

Battery:	9 V Block
Charging time:	10 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adaptor included:	US EURO CH UK
Operating time:	12 h
Operating time (Backlight off):	20 h
Rechargeable battery:	Rchrg. battery optional

Service

Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

Category

Brand:	KERN
Category:	Balances
Product Group:	Bench scale

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	340 x 400 x 190 mm
Gross weight:	2,950 kg
Net weight:	2,400 kg
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions housing (WxDxH):	270 x 323 x 110 mm
Dimensions of weighing plate (WxDxH):	252 x 228 x 12,5 mm
Material weighing plate:	Plastic
Weighing surface (WxD):	252 x 228 mm

Piktogramme

STANDARD



OPTION

