KERN FCF3K-4



Compact bench scale with multi-purpose functionality and a high level of accuracy for use in industry, gastronomy and kitchen



Measuring system	
Adjustment options:	External calibration
Linearity:	300 mg
Number of weighing ranges:	1
Readability [d]:	100 mg
Recommended adjusting weight:	2 kg (M1); 1 kg (M1)
Repeatability:	100 mg
Resolution:	30000
Stabilisation time under laboratory conditions:	3 s
Tare range:	3 kg
Warm up time:	2 h
Weighing capacity [Max]:	3 kg
Weighing system:	Strain gauge
Weighing units:	ozt tl (HK) tol g mo lb dwt oz tl (Tw)

Display digit height (large):	2,500 cm
Counting	
Counting resolution:	15000
Mininum piece weight at piece counting (Laboratory:	200 mg
Mininum piece weight at piece counting (Normal):	2 g

Display

Functions		
Counting function:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C

Power supply	
Battery:	9 V Block
Charging time:	16 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH UK US
Operating time:	20 h
Operating time (Backlight off):	120 h
Operating time (Backlight on):	80 h
Rechargeable battery:	Rchrg. battery optional - intern

Service	
Adjustment at the location of installation: 961-247	
DAkkS Certificate:	963-127

KERN
Balances
Bench scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	335 x 400 x 185 mm
Gross weight:	3,230 kg
Net weight:	2,630 kg
Shipping method:	Parcel service

Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	270 x 345 x 106 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	270 x 345 x 106 mm
Weighing surface (WxD):	253 x 228 mm

KERN FCF3K-4



Compact bench scale with multi-purpose functionality and a high level of accuracy for use in industry, gastronomy and kitchen

Piktogramme

STANDARD

















OPTION



