KERN FOB0.5K-4NS



Super compact stainless steel balance with high level of protection against dust and water splashes



Measuring system	
Adjustment options:	External calibration
Linearity:	200 mg
Number of weighing ranges:	1
Readability [d]:	100 mg
Recommended adjusting weight:	500 g (M1)
Repeatability:	100 mg
Resolution:	5000
Stabilisation time under laboratory conditions:	2 s
Tare range:	500 g
Warm up time:	10 min
Weighing capacity [Max]:	500 g
Weighing system:	Strain gauge
Weighing units:	ozt g lb dwt oz

Display

Display digit height (large):

Environmental conditions	
Maximum humidity:	95 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	10 °C
Minimum humidity:	25 %

2 cm

Power supply

Battery:	9 V Block		
Input voltage:	230 V AC 50 Hz		
Mains adapter:	Mains adapter external		
Operating time:	20 h		

Service

Adjustment at the location of installation: 961-247

DAkkS Certificate:

963-127

Brand:	KERN		
Category:	Balances		
Product Group:	Bench scale		
Packaging & shipping			
Delivery:	24 h		
Dimensions packaging (WxDxH):	255 x 195 x 75 mm		
Gross weight:	886 g		
Net weight:	760 g		
Shipping method:	Parcel service		
Construction			
Casing material:	stainless steel		
Dimensions housing (WxDxH):	170 x 150 x 40 mm		
Material weighing plate:	stainless steel		
Weighing surface (WxD):	120 x 150 mm		

STANDARD

	C	666	E C C C C C C C C C C C C C C C C C C C		
CAL EXT	UNIT	IP 65	BATT	DMS	1 DAY

OPTION

230 V +3 DAYS