KERN FOB 10K-3NL



Stainless steel bench scale with large weighing range and IP67 protection against dust and water splashes



Measuring system	
Adjustment options:	External calibration
Linearity:	3g 6g
Number of weighing ranges:	2
Readability [d]:	1g 2g
Recommended adjusting weight:	10 kg (M1)
Repeatability:	1g 2g
Resolution:	8 7.500
Stabilisation time under laboratory conditions:	2 s
Warm up time:	30 min 30 min
Weighing capacity [Max]:	8 kg 15 kg
Weighing system:	Strain gauge
Weighing units:	g lb oz

Display digit height (large):	2,500 cm
Environmental conditions	
Maximum humidity:	95 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C
Minimum humidity:	25 %

Power supply	
Battery:	4x1.5 V AA
Input voltage:	230 V AC 50 Hz
Mains adapter:	Mains adapter external
Operating time:	48 h

Service

Display

Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

Categor	ī.
Calegor	y

Brand: KERN
Category: Balances
Product Group: Bench scale

		0		
-/6/6	Zevalli	AYA D. 4	E 9.1 4	TIAVAL
Pac	ATA LUIII	■ r m = 0.1		

Delivery:	24 h
Dimensions packaging (WxDxH):	415 x 305 x 165 mm
Gross weight:	4,550 kg
Net weight:	3,750 kg
Shipping method:	Parcel service

Construction

Casing material:	stainless steel
Dimensions housing (WxDxH):	285 x 255 x 90 mm
Material weighing plate:	stainless steel
Weighing surface (WxD):	252 x 200 mm

Piktogramme

STANDARD



OPTION

