# KERN IFB600K-2



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg



## Measuring system

mededinig by stern				
Adjustment options:	External calibration			
Linearity:	60 g			
Load cell connection:	6-wire			
Readability [d]:	20 g			
Recommended adjusting weight:	600 kg (F2)			
Repeatability:	20 g			
Resolution:	30000			
Stabilisation time under laboratory conditions:	2 s			
Tare range:	-600 kg			
Warm up time:	2 h			
Weighing capacity [Max]:	600 kg			
Weighing system:	Strain gauge			
Weighing units:	kg			
Display				
Display digit height (large):	5,200 cm			
Counting				
Counting resolution:	30000			
Mininum piece weight at piece counting (Laboratory:	20 g			
Mininum piece weight at piece counting (Normal):	200 g			
Functions				
Counting function:	yes			
Function to save totals:	yes			
Vibration-free weighing (Animal weighing program):	yes			
Weighing with tolerance range:	yes			

Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0 %			
Power supply				
Charging time:	12 h			
Input voltage:	100 V - 240 V 50 / 60 Hz			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	US EURO CH UK			
Operating time (Backlight off):	35 h			
Operating time (Backlight on):	35 N 8 h			
Rechargeable battery:	•			
Recifargeable ballery.	Rchrg. battery optional (factory)			
Service				
Adjustment at the location of installation	n:961-250			
DAkkS Certificate:	963-130			
Category				
Brand:	KERN			
Category:	Balances			
Product Group:	Industiral scale			
Packaging & shipping				
	48 h			
Delivery:	48 h 1250 x 800 x 380 mm			
Delivery: Dimensions packaging (WxDxH):	1250 x 800 x 380 mm			
Delivery: Dimensions packaging (WxDxH): Gross weight:	1250 x 800 x 380 mm 70 kg			
Delivery: Dimensions packaging (WxDxH):	1250 x 800 x 380 mm			
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	1250 x 800 x 380 mm 70 kg 65 kg			
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	1250 x 800 x 380 mm 70 kg 65 kg Freight forwarder			
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device:	1250 x 800 x 380 mm 70 kg 65 kg Freight forwarder 3 m			
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material:	1250 x 800 x 380 mm 70 kg 65 kg Freight forwarder 3 m Plastic			
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device:	1250 x 800 x 380 mm 70 kg 65 kg Freight forwarder 3 m			
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device	1250 x 800 x 380 mm 70 kg 65 kg Freight forwarder 3 m Plastic			
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device (WxDxH): Dimensions of weighing plate	1250 x 800 x 380 mm 70 kg 65 kg Freight forwarder 3 m Plastic 250 x 160 x 58 mm			
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): Level indicator:	1250 x 800 x 380 mm 70 kg 65 kg Freight forwarder 3 m Plastic 250 x 160 x 58 mm 800 x 600 x 200 mm			
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	1250 x 800 x 380 mm 70 kg 65 kg Freight forwarder 3 m Plastic 250 x 160 x 58 mm 800 x 600 x 200 mm yes			
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): Level indicator: Material weighing plate:	1250 x 800 x 380 mm   70 kg   65 kg   Freight forwarder   3 m   Plastic   250 x 160 x 58 mm   800 x 600 x 200 mm   yes   stainless steel			
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): Level indicator: Material weighing plate: Overall dimensions mounted	1250 x 800 x 380 mm   70 kg   65 kg   Freight forwarder   3 m   Plastic   250 x 160 x 58 mm   800 x 600 x 200 mm   yes   stainless steel			
Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Casing material: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): Level indicator: Material weighing plate: Overall dimensions mounted (WxDxH):	1250 x 800 x 380 mm 70 kg 65 kg Freight forwarder 3 m Plastic 250 x 160 x 58 mm 800 x 600 x 200 mm yes stainless steel 800 x 600 x 190 mm			

# KERN IFB600K-2



High-resolution scale in heavy version with EC type approval [M], now also up to [Max] 600 kg

### Piktogramme

#### STANDARD

CAL EXT MULTI	RS 232	GLP PRINTER 2 DAYS	PCS	SUM	 MOVE	000 IP 65
OPTION						
DAkkS +3 DAYS						

### FACTORY

