KERN IXS 300 K-2



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system	
Adjustment options:	External calibration
Linearity:	30 g
Load cell connection:	6-wire
Number of weighing ranges:	1
Readability [d]:	10 g
Recommended adjusting weight:	300 kg (M1)
Repeatability:	10 g
Resolution:	30000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-300 kg
Warm up time:	2 h
Weighing capacity [Max]:	300 kg
Weighing system:	Strain gauge
Weighing units:	kg
Display	

Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	10 g
Mininum piece weight at piece counting (Normal):	100 g

5,500 cm

Display digit height (large):

Functions		
Counting function:	yes	
Data hold function:	yes	
Help function on the display:	yes	
Peak function:	yes	
PRE-TARE function:	yes	
Vibration-free weighing (Animal	yes	

Weighing with tolerance range:	yes	
Environmental conditions		

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power	supply

Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter/adapter included:	EURO
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional (factory)

Service

DAkkS Certificate:	963-129
DAKKS CELIIICAIE.	303-123

Category

Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & shipping	
Delivery:	48 h
Dimensions packaging (WxDxH):	940 x 600 x 250 mm
Gross weight:	38 kg
Net weight:	35 kg
Shipping method:	Freight forwarder

Construction	
Cable length of display device:	2,500 m
Dimensions of display device (WxDxH):	232 x 150 x 80 mm
Dimensions of weighing plate (WxDxH):	650 x 500 x 133,5 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	650 x 500 mm

weighing program): KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49–(0)7433 - 99 33-0 · www.kern-sohn.com

KERN IXS 300 K-2



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Piktogramme STANDARD TOL MOVE IP 65 IP 68 230 V CAL EXT PCS SUM 1 DAY 2 DAYS **OPTION** DAkkS +3 DAYS **FACTORY** - 888 · ARRA · RS 232 RS 485 ACCU +3 DAYS