KERN IXS30K-3L



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Adjustment options:	External calibration
Linearity:	3 g
Load cell connection:	6-wire
Number of weighing ranges:	1
Readability [d]:	1 g
Recommended adjusting weight:	30 kg (M1)
Repeatability:	1 g
Resolution:	30000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-30 kg
Warm up time:	2 h
Weighing capacity [Max]:	30 kg
Weighing system:	Strain gauge
Weighing units:	kg

Counting		
Counting resolution:	30000	
Mininum piece weight at piece counting (Laboratory:	1 g	
Mininum piece weight at piece counting (Normal):	10 g	

5,500 cm

Display digit height (large):

Functions		
Counting function:	yes	
Data hold function:	yes	
Help function on the display:	yes	
Peak function:	yes	
PRE-TARE function:	yes	
Vibration-free weighing (Animal	yes	

Weighing with tolerance range:	yes	
Environmental conditions		
Maximum humidity:	80 %	
Maximum operating temperature:	40 °C	

Maximum mumuty.	00 /0
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter/adapter included:	EURO
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional (factory)

OCIVICO
Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	500 x 775 x 240 mm
Gross weight:	23 kg
Net weight:	20,500 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	2,500 m
Dimensions of display device (WxDxH):	232 x 150 x 80 mm
Dimensions of weighing plate (WxDxH):	500 x 400 x 123 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	500 x 400 mm

KERN IXS30K-3L



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Piktogramme STANDARD MOVE IP 65 IP 68 TOL 230 V CAL EXT PCS SUM 1 DAY 2 DAYS **OPTION** DAkkS +3 DAYS **FACTORY** - ARRA · ARRA · RS 232 RS 485 ACCU +3 DAYS