

KERN KDP 300-3

Universal weighing platforms for flexible connection in process chains



Construction

| | |
|---------------------------------------|--------------------|
| Cable length: | 1,200 m |
| Cable length of display device: | 1,500 m |
| Dimensions draft shield (WxDxH): | 157 x 157 x 80 mm |
| Dimensions housing (WxDxH): | 165 x 166 x 75 mm |
| Dimensions of display device (WxDxH): | 0 x 0 x 0 mm |
| Dimensions of weighing plate (WxDxH): | 165 x 165 x 73 mm |
| Level indicator: | yes |
| Overall dimensions mounted (WxDxH): | 165 x 166 x 140 mm |
| Revolving screw feet: | yes |
| Weighing space (WxDxH): | 146 x 146 x 80 mm |
| Weighing surface (d): | 105 |

Piktogramme

STANDARD



OPTION



FACTORY



Measuring system

| | |
|--------------------------|----------------------|
| Adjustment options: | External calibration |
| Linearity: | 5 mg |
| Readability [d]: | 1 mg |
| Repeatability: | 2 mg |
| Resolution: | 350000 |
| Warm up time: | 2 h |
| Weighing capacity [Max]: | 350 g |
| Weighing system: | Strain gauge |

Environmental conditions

| | |
|--------------------------------|-------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 35 °C |
| Minimum ambient temperature: | 5 °C |

Power supply

| | |
|----------------|--------------------------|
| Input voltage: | 100 V - 240 V 50 / 60 Hz |
|----------------|--------------------------|

Service

| | |
|--------------------|---------|
| DAkkS Certificate: | 963-127 |
|--------------------|---------|

Category

| | |
|--------|------|
| Brand: | KERN |
|--------|------|

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 250 x 510 x 165 mm |
| Net weight: | 1,040 kg |
| Shipping method: | Parcel service |