

# KERN KGP 30K-3L



Robust industrial platform scale with digital scale transmitter, ideal for varied range of applications for Industry 4.0



## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

## Power supply

Battery:	no battery
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter/adaptor included:	EURO UK

## Service

Adjustment at the location of installation:	961-248
DAkkS Certificate:	963-128

## Category

Brand:	KERN
Product Group:	Industrial scale

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	465 x 795 x 230 mm
Gross weight:	12 kg
Net weight:	9,800 kg
Shipping method:	Parcel service

## Construction

Cable length of display device:	2,500 m
Casing material:	Plastic
Dimensions of display device (WxDxH):	250 x 160 x 58 mm
Dimensions of weighing plate (WxDxH):	400 x 300 x 128 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	400 x 300 mm

## Measuring system

Adjustment options:	External calibration
Linearity:	4 g
Load cell connection:	6-wire
Number of weighing ranges:	1
Readability [d]:	1 g
Recommended adjusting weight:	30 kg (F2)
Repeatability:	1 g
Resolution:	30000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-30 kg
Warm up time:	2 h
Weighing capacity [Max]:	30 kg
Weighing system:	Strain gauge
Weighing units:	kg t g

## Display

Display digit height (large):	5,200 cm
-------------------------------	----------

## Counting

Counting resolution:	30000
Minimum piece weight at piece counting (Laboratory):	1 g
Minimum piece weight at piece counting (Normal):	10 g

## Functions

PRE-TARE function:	yes
--------------------	-----

# KERN KGP 30K-3L



Robust industrial platform scale with digital scale transmitter, ideal for varied range of applications for Industry 4.0

## Piktogramme

### STANDARD



### OPTION



### FACTORY

