KERN MCC250K100M



Ergonomically optimised chair scale with EC type approval and approval for medical use for professional use in medical diagnostics



Measuring system	
Adjustment options:	External calibration
Linearity:	100 g
Readability [d]:	100 g
Recommended adjusting weight:	200 kg (M1)
Repeatability:	100 g
Resolution:	2500
Stabilisation time under laboratory conditions:	3 s
Tare range:	249,900 kg
Warm up time:	10 min
Weighing capacity [Max]:	250 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display		
Display digit height (large):	2,500 cm	

Technical data about verification		
Minimum load [Min]:	2 kg	
Periodic Verification for Italy:	969-112	
Verification approval conforming to 2014/31/EU:	yes	
Verification by KERN possible:	yes	
Verification class:	III	
Verification value [e]:	100 g	

Functions		
BMI function:	yes	
Data hold function:	yes	
Vibration-free weighing (Animal weighing program):	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	10 °C

Power supply	
Battery:	6x1.5 V AA
Charging time:	12 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH UK
Operating time:	20 h
Operating time (Backlight off):	40 h
Operating time (Backlight on):	20 h
Operating time: Operating time (Backlight off):	20 h 40 h

Service
Adjustment at the location of installation: 961-249

DAkkS Certificate:	963-129
Verification:	965-129

Category	
Brand:	KERN
Category:	Balances
Product Group:	Chair scale

Packaging & shipping	
Delivery:	48 h
Dimensions packaging (WxDxH):	1080 x 690 x 1080 mm
Gross weight:	37,500 kg
Net weight:	23,300 kg
Shipping method:	Freight forwarder

Construction	
Casing material:	Steel lacquered
Dimensions of display device (WxDxH):	200 x 130 x 60 mm
Dimensions of weighing plate (WxDxH):	502 x 380 x 410 mm
Level indicator:	yes
Material weighing plate:	Plastic
Overall dimensions mounted (WxDxH):	625 x 990 x 985 mm

KERN MCC250K100M



Ergonomically optimised chair scale with EC type approval and approval for medical use for professional use in medical diagnostics

Weighing surface (WxD): 390 x 360 mm

Piktogramme

STANDARD

MOVE BATT

ACCU

MULTI 1 DAY

OPTION

DAkkS +3 DAYS

FACTORY

