# KERN RIB30K-2M



High-quality retail scale with large item memory and user-friendly concept of operation



### Measuring system

5	
Adjustment options:	External calibration
Linearity:	5 g   10 g
Number of weighing ranges:	2
Readability [d]:	5 g   10 g
Recommended adjusting weight:	30 kg (M1)
Repeatability:	5 g   10 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	30 kg
Warm up time:	10 min   10 min
Weighing capacity [Max]:	15 kg   30 kg
Weighing system:	Strain gauge
Weighing units:	kg g
Display	
Additional Display possible:	yes
Display digit height (large):	1,800 cm
Technical data about verification	
Minimum load [Min]:	100 g   200 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes

to 2014/31/EU:		
Verification by KERN possible:	yes	
Verification class:	III	
Verification value [e]:	5g 10g	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %
Power supply	
Battery:	no battery
Charging time:	14 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH UK
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional - intern
Service	
Adjustment at the location of installati	on:961-248
DAkkS Certificate:	963-128
Verification:	965-228
Category	
Brand:	KERN
Category:	Balances
Product Group:	Price computing scale
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	380 x 380 x 155 mm
Gross weight:	4,500 kg
Net weight:	3,200 kg
Shipping method:	Parcel service
Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	325 x 340 x 115 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	325 x 340 x 115 mm
Revolving screw feet:	yes
Weighing surface (WxD):	294 x 225 mm

## KERN RIB30K-2M



High-quality retail scale with large item memory and user-friendly concept of operation

#### Piktogramme

#### STANDARD



OPTION



FACTORY

