

KERN RIB6K-3HM

High-quality retail scale with large item memory and user-friendly concept of operation



Measuring system

| | |
|---|----------------------|
| Adjustment options: | External calibration |
| Linearity: | 1 g 2 g |
| Number of weighing ranges: | 2 |
| Readability [d]: | 1 g 2 g |
| Recommended adjusting weight: | 5 kg (F2); 1 kg (F2) |
| Repeatability: | 1 g 2 g |
| Resolution: | 3 3.000 |
| Stabilisation time under laboratory conditions: | 2 s |
| Tare range: | 6 kg |
| Warm up time: | 10 min 10 min |
| Weighing capacity [Max]: | 3 kg 6 kg |
| Weighing system: | Strain gauge |
| Weighing units: | kg g |

Display

| | |
|-------------------------------|----------|
| Additional Display possible: | yes |
| Display digit height (large): | 1,800 cm |

Technical data about verification

| | |
|---|-------------|
| Minimum load [Min]: | 20 g 40 g |
| Periodic Verification for Italy: | 969-112 |
| Verification approval conforming to 2014/31/EU: | yes |
| Verification by KERN possible: | yes |
| Verification class: | III |
| Verification value [e]: | 1 g 2 g |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -10 °C |
| Minimum humidity: | 0 % |

Power supply

| | |
|---------------------------------|-------------------------------------|
| Battery: | no battery |
| Charging time: | 14 h |
| Input voltage: | 100V-240V AC 50/60Hz 0,400 Amax |
| Mains adapter: | Mains adapter external |
| Mains adapter/adaptor included: | EURO CH UK |
| Operating time (Backlight off): | 80 h |
| Operating time (Backlight on): | 40 h |
| Rechargeable battery: | Rchrg. battery optional - intern |

Service

Adjustment at the location of installation: 961-248

| | |
|--------------------|---------|
| DAkkS Certificate: | 963-128 |
| Verification: | 965-228 |

Category

| | |
|----------------|-----------------------|
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Price computing scale |

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 450 x 400 x 210 mm |
| Gross weight: | 5,500 kg |
| Net weight: | 3,800 kg |
| Shipping method: | Parcel service |

Construction

| | |
|--------------------------------------|---------------------------------|
| Casing material: | Plastic |
| Dimensions housing (WxDxH) of stand: | 325 x 340 x 115 mm 40,500 cm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Overall dimensions mounted (WxDxH): | 325 x 340 x 405 mm |
| Revolving screw feet: | yes |
| Weighing surface (WxD): | 294 x 225 mm |

KERN RIB6K-3HM

High-quality retail scale with large item memory and user-friendly concept of operation



Piktogramme

STANDARD



OPTION



FACTORY

