KERN SFB100K-2XL



Stainless steel platform scales with IP65 protection, also with XL platform or EC type approval [M]



Measuring system				
Adjustment options:	External calibration			
Linearity:	20 g			
Load cell connection:	6-wire			
Readability [d]:	10 g			
Recommended adjusting weight:	100 kg (M1)			
Repeatability:	10 g			
Resolution:	10000			
Stabilisation time under laboratory conditions:	2 s			
Tare range:	100 kg			
Warm up time:	30 min			
Weighing capacity [Max]:	100 kg			
Weighing system:	Strain gauge			
Weighing units:	kg			
Display				
Display digit height (large):	5,200 cm			
Functions				
Counting function:	yes			
Function to save totals:	yes			
Vibration-free weighing (Animal weighing program):	yes			
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	95 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			

Minimum humidity:

Power supply				
Charging time:	12 h			
Input voltage:	110 V - 230 V AC			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	US EURO CH UK			
Operating time (Backlight off):	35 h			
Operating time (Backlight on):	20 h			
Service				
Adjustment at the location of installation	:961-249			
DAkkS Certificate:	963-129			
Category				
Brand:	KERN			
Category:	Balances			
Product Group:	Industiral scale			
Packaging & shipping				
Delivery:	24 h			
Delivery: Dimensions packaging (WxDxH):	24 h 1045 x 675 x 250 mm			
•				
Dimensions packaging (WxDxH):	1045 x 675 x 250 mm			
Dimensions packaging (WxDxH): Gross weight:	1045 x 675 x 250 mm 27,300 kg			
Dimensions packaging (WxDxH): Gross weight: Net weight:	1045 x 675 x 250 mm 27,300 kg 24,500 kg			
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	1045 x 675 x 250 mm 27,300 kg 24,500 kg Parcel service			
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number: Construction	1045 x 675 x 250 mm 27,300 kg 24,500 kg Parcel service			
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number:	1045 x 675 x 250 mm 27,300 kg 24,500 kg Parcel service 2800			
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number: Construction Cable length of display device:	1045 x 675 x 250 mm 27,300 kg 24,500 kg Parcel service 2800 3 m			
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate	1045 x 675 x 250 mm 27,300 kg 24,500 kg Parcel service 2800 3 m			
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	1045 x 675 x 250 mm 27,300 kg 24,500 kg Parcel service 2800 3 m 266 x 165 x 96 mm 650 x 500 x 142 mm			
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): Level indicator:	1045 x 675 x 250 mm 27,300 kg 24,500 kg Parcel service 2800 3 m 266 x 165 x 96 mm 650 x 500 x 142 mm yes			
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): Level indicator: Material weighing plate:	1045 x 675 x 250 mm 27,300 kg 24,500 kg Parcel service 2800 3 m 266 x 165 x 96 mm 650 x 500 x 142 mm yes stainless steel			
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): Level indicator:	1045 x 675 x 250 mm 27,300 kg 24,500 kg Parcel service 2800 3 m 266 x 165 x 96 mm 650 x 500 x 142 mm yes			
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): Level indicator: Material weighing plate: Overall dimensions mounted	1045 x 675 x 250 mm 27,300 kg 24,500 kg Parcel service 2800 3 m 266 x 165 x 96 mm 650 x 500 x 142 mm yes stainless steel			
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: UN number: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): Level indicator: Material weighing plate: Overall dimensions mounted (WxDxH):	1045 x 675 x 250 mm 27,300 kg 24,500 kg Parcel service 2800 3 m 266 x 165 x 96 mm 650 x 500 x 142 mm yes stainless steel 650 x 660 x 590 mm			

0%

KERN SFB100K-2XL



Stainless steel platform scales with IP65 protection, also with XL platform or EC type approval [M]

Piktogramme

STANDARD

КСР	GLP			-√+ ⊙ ?))	666	666	
CAL EXT PROTOCOL	PRINTER	PCS	SUM	TOL	IP 65	IP 67	ACCU
MULTI DMS	1 DAY						

OPTION

DAkks +3 days

FACTORY

