KERN SFB60K20LHIPM



Stainless steel platform balance with dust and spray protection to IP65 and EC type approval [M]



Measuring system

Adjustment options:	External calibration
Linearity:	20 g
Load cell connection:	6-wire
Readability [d]:	20 g
Recommended adjusting weight:	60 kg (M1)
Repeatability:	20 g
Resolution:	3000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-60 kg
Warm up time:	10 min
Weighing capacity [Max]:	60 kg
Weighing system:	Strain gauge
Weighing units:	kg
Display	

Display digit height (large):

5,200 cm

Technical data about verificationMinimum load [Min]:400 gPeriodic Verification for Italy:969-112Verification approval conforming to 2014/31/EU:yesVerification by KERN possible:yesVerification class:IIIVerification value [e]:20 gFunctionsCounting function:yesFunction to save totals:yes		
Periodic Verification for Italy:969-112Verification approval conforming to 2014/31/EU:yesVerification by KERN possible:yesVerification class:IIIVerification value [e]:20 gFunctionsCounting function:yes		
Verification approval conforming to 2014/31/EU:yesVerification by KERN possible:yesVerification class:IIIVerification value [e]:20 gFunctionsCounting function:yes		
to 2014/31/EU: Verification by KERN possible: yes Verification class: III Verification value [e]: 20 g Functions Counting function: yes		
Verification class: III Verification value [e]: 20 g Functions Counting function: yes		
Verification value [e]: 20 g Functions Counting function: yes		
Functions Counting function: yes		
Counting function: yes		
Function to save totals: ves		
y co		
Vibration-free weighing (Animal yes weighing program):		
Weighing with tolerance range: yes		
Environmental conditions		
Maximum humidity: 95 %		
Maximum operating temperature: 40 °C		
Minimum ambient temperature: -10 °C		
Minimum humidity: 0 %		
Power supply		
Charging time: 12 h		
Input voltage: 110 V - 230 V AC		
Mains adapter: Mains adapter external		
Mains adapter/adapter included: US EURO CH UK		
Operating time (Backlight off): 35 h		
Operating time (Backlight on): 20 h		
Service		
Adjustment at the location of installation: 961-249		
DAkkS Certificate: 963-129		
Verification: 965-229		
Category		
Brand: KERN		
Category: Balances		
Product Group: Industiral scale		
Packaging & shipping		
Delivery: 24 h		
Dimensions packaging (WxDxH): 470 x 800 x 240 mm		
Gross weight: 14,700 kg		
Net weight: 14 kg		
Shipping method: Parcel service		
UN number: 2800		

KERN SFB60K20LHIPM

Stainless steel platform balance with dust and spray protection to IP65 and EC type approval [M]



Construction

Cable length of display device:	0 mm
Dimensions of display device (WxDxH):	266 x 165 x 96 mm
Dimensions of weighing plate (WxDxH):	400 x 300 x 128 mm
of stand:	40 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	400 x 460 x 590 mm
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	400 x 300 mm

Piktogramme

STANDARD



OPTION



FACTORY

