

# KERN SFE6K-3NM

Platform scale with dust and spray protection IP65 and EC type approval [M]



## Measuring system

Adjustment options:	External calibration
Linearity:	2 g
Readability [d]:	2 g
Recommended adjusting weight:	6 kg (M1)
Repeatability:	2 g
Resolution:	3000
Stabilisation time under laboratory conditions:	2 s
Tare range:	5,998 kg
Warm up time:	10 min
Weighing capacity [Max]:	6 kg
Weighing system:	Strain gauge
Weighing units:	kg

## Display

Display digit height (large):	2,200 cm
-------------------------------	----------

## Technical data about verification

Minimum load [Min]:	40 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	2 g

## Functions

Function to save totals:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

## Power supply

Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO UK US
Operating time (Backlight off):	35 h
Operating time (Backlight on):	10 h

## Service

Adjustment at the location of installation:	961-248
DAkkS Certificate:	963-128
Verification:	965-228

## Category

Brand:	KERN
Category:	Balances
Product Group:	Industrial scale

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	412 x 695 x 220 mm
Gross weight:	6,785 kg
Net weight:	5,700 kg
Shipping method:	Parcel service
UN number:	3496

## Construction

Cable length:	2,500 m
Cable length of display device:	3 m
Dimensions of display device (WxDxH):	195 x 120 x 70 mm
Dimensions of weighing plate (WxDxH):	300 x 240 x 110 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	300 x 240 mm

# KERN SFE6K-3NM

Platform scale with dust and spray protection IP65 and EC type approval [M]



## Piktogramme

### STANDARD



### OPTION



### FACTORY

