

# KERN SW2000

Professional sound level meters of class I and class II in premium quality



## Category

|                |                    |
|----------------|--------------------|
| Brand:         | Sauter             |
| Category:      | Sound level meters |
| Product Group: | Sound level meter  |

## Packaging & shipping

|                               |                   |
|-------------------------------|-------------------|
| Delivery:                     | 24 h              |
| Dimensions packaging (WxDxH): | 350 x 280 x 90 mm |
| Gross weight:                 | 1,300 kg          |
| Net weight:                   | 700 g             |
| Shipping method:              | Parcel service    |

## Construction

|                                     |                  |
|-------------------------------------|------------------|
| Casing material:                    | Plastic          |
| Dimensions device (WxDxH):          | 300 x 80 x 36 mm |
| Dimensions housing (WxDxH):         | 300 x 80 x 36 mm |
| Overall dimensions mounted (WxDxH): | 300 x 80 x 36 mm |

## Piktogramme

### STANDARD



### OPTION



## Measuring system

|                           |          |
|---------------------------|----------|
| Measuring capacity [Max]: | 136 db   |
| Readability [d]:          | 0,100 db |
| Weighing units:           | dB       |

## Functions

|                         |     |
|-------------------------|-----|
| Data hold function:     | yes |
| Function to set limits: | yes |
| Peak function:          | yes |
| Visual ready signal:    | yes |

## Environmental conditions

|                                |        |
|--------------------------------|--------|
| Maximum operating temperature: | 50 °C  |
| Minimum operating temperature: | -10 °C |

## Power supply

|                                 |                          |
|---------------------------------|--------------------------|
| Battery:                        | 4x1.5 V AA               |
| Input voltage:                  | 100 V - 240 V 50 / 60 Hz |
| Mains adapter:                  | Mains adapter external   |
| Mains adapter/adaptor included: | EURO                     |
| Operating time:                 | 10 h                     |

## Service

|                                  |         |
|----------------------------------|---------|
| DAkkS Certificate:               | 963-281 |
| Factory calibration certificate: | 961-281 |